NEW .XICO OIL CONSERVATION COMM. ON

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or its agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

owed, and work should not begin until approval is obtain f the Commission. Indicate nature of	of notice by checking below:
OTICE OF INTENTION TO TEST CASING SHUT-OFF	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL
NOTICE OF INTENTION TO CHANGE PLANS	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING
OTICE OF INTENTION TO REPAIR WELL	NOTICE OF INTENTION TO PLUG WELL
OTICE OF INTENTION TO DEEPEN WELL	
Monument, New Mea	rico February 8, 1956
IL CONSERVATION COMMISSION, anta Fe, New Mexico.	- Place Date
blowing is a notice of intention to do certain work as merada Potroleum Corporation	described below at the Well No. 1 in 1882 SW
Company or Operator Lease Sec. 25 T. 19 R. 36	
County,	, N. M. P. M., Equipment Fie
FOLLOW INSTRUCTIONS IN THE RUL 5/8" 36# 8-thd. New Seemless easing w the Halliburten method with 500 sack sing and fittings will be tested with r thirty minutes undisturbed. General	1200# pump pressure and allowed to stand
FOLLOW INSTRUCTIONS IN THE RULE 15/8" 36# 8-thd. New Seemless easing we the Halliburten method with 500 mack using and fittings will be tested with a thirty minutes undisturbed. Gement in the same test again applied and allowed.	LES AND REGULATIONS OF THE COMMISSION TAS Set in this well at 2470' and cemented S coment. 1200# pump pressure and allowed to stand plug will then be drilled out of casing owed to stand undisturbed for thirty minutes g will be resumed.
of/8" 36# 8-thd. New Seemless casing we the Halliburten method with 500 sack using and fittings will be tested with a thirty minutes undisturbed. Coment is the same test again applied and allow there is no drop in pressure drilling.	LES AND REGULATIONS OF THE COMMISSION TABLE SET IN this well at 2470' and comented Sement. 1200f pump pressure and allowed to stand plug will then be drilled out of casing
FEB 1 4 1936 FEB 1 4 1936 FEB 1 4 1936 FEB 1 4 1936	LES AND REGULATIONS OF THE COMMISSION TAS Set in this well at 2470' and cemented S coment. 1200# pump pressure and allowed to stand plug will then be drilled out of casing owed to stand undisturbed for thirty minutes g will be resumed.
FEB 1 4 1936 FEB 1 4 1936 FEB 1 4 1936 FEB 1 4 1936	LES AND REGULATIONS OF THE COMMISSION Tas set in this well at 2470' and cemented Sement. 1200f pump pressure and allowed to stand plug will then be drilled out of casing owed to stand undisturbed for thirty minutes S will be resumed. Company or Operator Company or Operator
FEB 1 4 1936 FEB 1 4 1936 FEB 1 4 1936 FEB 1 4 1936	LES AND REGULATIONS OF THE COMMISSION The second of this well at 2470' and cemented to stand the second of the stand plug will then be drilled out of casing own to stand undisturbed for thirty minutes will be resumed. Amerada Petroleum Corporation Company or Operator By A. Markey
FEB 1 4 1936 FEB 1 4 1936 FEB 1 4 1936	LES AND REGULATIONS OF THE COMMISSION Tas set in this well at 2470' and cemented Sement. 1200f pump pressure and allowed to stand plug will then be drilled out of casing owed to stand undisturbed for thirty minutes S will be resumed. Company or Operator Company or Operator
FEB 1 4 1936 FEB 1 4 1936 proved	LES AND REGULATIONS OF THE COMMISSION Tas set in this well at 2470' and comented Be coment. 1200f pump pressure and allowed to stand plug will then be drilled out of casing owed to stand undisturbed for thirty minutes Will be resumed. DUPLICATE Amerada Petroleum Corporation Company or Operator By Adamses Position Farm Boss
of/8" 36# 8-thd. New Seemless easing we the Halliburten method with 500 sack using and fittings will be tested with a thirty minutes undisturbed. Coment is the same test again applied and allow there is no drop in pressure drilling.	Amerada Petroleum Corporation Company or Operator By Communications regarding well to Send communications regarding well to

ICK

ME TO VIEW OF AN ALMAND THE CONTRACTOR OF THE SECOND STREET, THE SECON

ALL: A REALESTA LICE

The control of the co

and the second of the second o

a de la composition La composition de la La composition de la

on the second of the second of

att. C

ara in this control of the control o

in de establica de la companya de l Establica de la companya de la comp Establica de la companya de la comp

en de la composition de la composition

(x,y) = (x,y) + (y,y) = (x,y) + (y,y) + (y,y) = (y,y) + (y,y

igaaku nya manine ninan-

•