

NEW MEXICO STATE #1
LEA COUNTY

6. MIRU McCULLOUGH. PERF GRAYBURG 3865-70, 3883-89, 3896-3905, 3912-3925', 1 JSPF, TOTAL 37 HOLES, VIA ATLAS CORP GR/NEUTRON LOG DATED 4/15/54, USING 4" OD, 22.5 GC, 0.53" EH CSG GUN.
7. MIRU BJ-TITAN. RIH W/ 5-1/2 x 2-3/8 "PFT" ON 2-3/8" PROD TBG. NU STRIPPING HEAD. ROUNDTrip TOOL THRU PERFS 3865-3925' IN CIRC MODE USING NE 2% KCL FRSH WTR. SPOT 3000 GALS 15% NEFE HCL W/ ADDITIVES TO TOOL. CONTINUE MOVING TOOL THRU PERFS IN INJ MODE. IF CIRC NOT ESTAB, FLUSH BACKSIDE W/ NE 2% KCL. ND STRIPPING HEAD. POH W/ PFT.
8. RIH W/ 2-3/8" PROD TBG SETUP AS BEFORE. ND BOP. NU WH. RIH W/ 2"x1.5x16 RHBC ROD PUMP (10' GAS ANCHOR) ON '66' TAPER ROD STRING AS BEFORE. RESPACE AS NECESSARY. CHECK PUMP ACTION. RLSE RIG.
9. PUT ON PRODUCTION @ 1.5 x 54 x 17 (207 BPD PUMP CAPACITY).