Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or its agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations

	indicate nature	of notice	by checking below:	
NOTICE OF INTENT	TION TO TEST CASING SHUT-OFF	x	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENT	FION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTEN	TION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG W ELL	
NOTICE OF INTENT	TION TO DEEPEN WELL			
	Monument, N	lew Mexi	Place November 8, 19	36
II. CONSERVATE	ON COMMISSION,		Place Date	
anta Fe, New Mex				
entlemen:				
	ce of intentiton to do certain wor			
Company or One	erator Lease	Weir	Well No 7 in SW	583
Company or Ope			M. P. M., Momment	_
Da.	County.	,		Fie
	•			
	reon menton elth 200 880	CKS.	t in this well at 2555 and com	
sing and fit: r thirty mine drilled out d allowed to	tings will be tested with ates, undisturbed. If a of the casing and the s	th 1200# no drop	pump pressure and allowed to a in pressure results the coment to 1200# pump pressure again a inutes. If no drop in pressure	tand
sing and fit: or thirty mine drilled out d allowed to	tings will be tested with the state of the casing and the stand undisturbed for the stand undist	th 1200# no drop	pump pressure and allowed to a in pressure results the cement with the comment of 1800#	tand
asing and fit- or thirty mine drilled out d allowed to e drilling wi	tings will be tested with ates, undisturbed. If r of the casing and the stand undisturbed for till then be resumed	th 1200# no drop	pump pressure and allowed to a in pressure results the cement of 1200# pump pressure again a inutes. If no drop in pressure	tand will th applied result
asing and fitter thirty minus drilled out dallowed to drilling with the drilling wit	tings will be tested with the state of the casing and the stand undisturbed for the stand undist	th 1200# no drop	pump pressure and allowed to a in pressure results the cement with the comment of 1800#	tand will th applied result
asing and fitter thirty minus drilled out dallowed to drilling with the drilling wit	tings will be tested with ates, undisturbed. If r of the casing and the stand undisturbed for till then be resumed	th 1200# no drop same tes	pump pressure and allowed to sin pressure results the cement of 1200# pump pressure again a inutes. If no drop in pressure	tand will th applied result
asing and fitter thirty minus drilled out dallowed to drilling with the drilling wit	tings will be tested with ates, undisturbed. If r of the casing and the stand undisturbed for till then be resumed	th 1200# no drop same tes thirty m	pump pressure and allowed to sin pressure results the cement of 1200# pump pressure again a inutes. If no drop in pressure Amerada Petroleum Corporat Company or Operator	tand will th applied result
asing and fitter thirty minus drilled out dallowed to drilling with the drilling wit	tings will be tested with ates, undisturbed. If r of the casing and the stand undisturbed for till then be resumed	th 1200# no drop same tes thirty m	pump pressure and allowed to sin pressure results the cement of 1200# pump pressure again a inutes. If no drop in pressure Amerada Petroleum Corporat Company or Operator Y	tand will th applied result
asing and fit: or thirty minus odrilled out ad allowed to	tings will be tested with ates, undisturbed. If a of the casing and the a stand undisturbed for tall them be resumed	th 1200# no drop same tes thirty m	pump pressure and allowed to sin pressure results the cement of 1200# pump pressure again a inutes. If no drop in pressure Company or Operator Y Osition Farm Boss	tand will th applied result
asing and fitter thirty mine drilled out dallowed to drilling with the drilling with	tings will be tested with ates, undisturbed. If a of the casing and the a stand undisturbed for tall them be resumed	th 1200# no drop same tes thirty m	pump pressure and allowed to an in pressure results the cement of 1200# pump pressure again a inutes. If no drop in pressure Company or Operator y Company or Operator y Osition Farm Boss Send communications regarding well	tand will th applied result

and the second s

and the second

 $(x_{i,j}, \dots, x_{i,j}) \in \mathcal{H}_{i+1} \times \mathcal{H}_$ $\mathcal{F}_{i,j} = \{ (i,j) \in \mathcal{F}_{i,j} : i \in \mathcal{F}_{i,j} \text{ for } i \in \mathcal{F}_{i,j} \text$

t ·

garanta da la composição de la composição

grande grande i de la companya de l La companya de la co