

NO. OF COPIES RECEIVED		
DISTRIBUTION		
UNIT A FE		
ILE		
S.G.S.		
AND OFFICE		
PERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REPERF OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR REPORT ON WELLS C-101 FOR SUCH PROPOSALS.)	
OIL WELL ☒ GAS WELL ☐ OTHER ☐	5a. Indicate Type of Lease State ☐ Fee ☒
Name of Operator Amerada Hess Corporation	5. State Oil & Gas Lease No.
Address of Operator Drawer D, Monument, New Mexico 88265	7. Unit Agreement Name
Location of Well UNIT LETTER G 1980 FEET FROM THE North LINE AND 1980 FEET FROM East THE 26 LINE, SECTION 19-S TOWNSHIP 36-E RANGE NMPM.	8. Farm or Lease Name W. A. Weir "B"
10. Field and Pool, or Wildcat Monument - G/SA	9. Well No. 1
11. Elevation (Show whether DF, RT, GR, etc.) 3675' DF	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK ☐ TEMPORARILY ABANDON ☐ PLUG OR ALTER CASING ☐ OTHER ☐	SUBSEQUENT REPORT OF: PLUG AND ABANDON ☐ CHANGE PLANS ☐ OTHER ☐
REMEDIAL WORK ☒ COMMENCE DRILLING OPNS. ☐ CASING TEST AND CEMENT JOB ☐ OTHER ☐	ALTERING CASING ☐ PLUG AND ABANDONMENT ☐ OTHER ☒

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

January - February 1979

Pulled rods, pump, 1-1/2" tbg. & 3-1/2" tbg. & pkr. Ran 3-5/8" junk basket to 3865'. Set bridge plug in 4-1/2" liner at 3857'. Tested bridge plug w/1500# press. Held OK. Set cement retainer in 6-5/8" csg. at 3434'. Tested tbg/ w.2000# press. Held OK. Pressured 6-5/8" csg. to 500#. Dowell squeezed Eumont Queen zone thru 6-5/8" csg. perf. fr. 3565' to 3729' w/300 sks. cement w/additives. Reversed out 8 sks. cement, left 239 sks. cement in formation & 53 sks. cement inside 6-5/8" csg. WOC & drld. retainer & firm cement fr. 3448' to 3781'. Tested squeeze job w/800# press. f/20 min. Held OK. Drld. & pushed bridge plug fr. 3857' to 4017'. McCullough re-perf. 4-1/2" liner opposite Grayburg San Andres zone fr. 3972' to 3995'. Set pkr. in 4-1/2" liner at 3942'. Tested tbg. w/2000# press. Held OK. Loaded annulus w/50/50 brine water. Dowell acidized Grayburg San Andres zone thru 4-1/2" liner perf. fr. 3972' to 3995' w/2000 gal. 20% NE acid & flushed w/50/50 brine water. Swabbed load. Re-ran 2-3/8" tbg., pump & rods & resumed production as pumping Grayburg San Andres oil well.

Test of 2-27-79: Pumped 23 b.o. & 28 b.w. in 24 hrs. on 9-44" SPM.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED E. B. Fisher TITLE Supv. Adm. Ser. DATE 2-27-79

APPROVED BY Jerry Sexton TITLE Asst. 1, Supv. DATE MAR 2 1979

CONDITIONS OF APPROVAL, IF ANY