

NO. OF COPIES RECEIVED	
DISTRIBUTION	
ALTA FE	
FILE	
J.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL <input checked="" type="checkbox"/>	GAS WELL <input type="checkbox"/>	OTHER- <input type="checkbox"/>
Name of Operator Gulf Oil Corporation		
Address of Operator P. O. Box 670, Hobbs, N.M. 88240		
Location of Well UNIT LETTER <u>P</u> <u>660</u> FEET FROM THE <u>south</u> LINE AND <u>660</u> FEET FROM THE <u>east</u> LINE, SECTION <u>26</u> TOWNSHIP <u>19S</u> RANGE <u>36E</u> NMPM.		

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Farm or Lease Name C. T. Bates
9. Well No. 11
10. Field and Pool, or Wildcat Eunice-Monument
12. County Lea

15. Elevation (Show whether DF, RT, GR, etc.) 3648' GL

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Opened well up and swabbed dry, no commercial production. Plugged and abandoned as follows:

Pulled equipment out of hole. Went in hole with CIBP and set at 3600'. Circulated hole with 140 barrels of abandonment fluid. Tested casing with 500# 30 minutes, OK. Spotted 7 sacks Class H cement plug on top of BP at 3565' to 3600'. Spotted 20 sacks Class H cement plug from 1116' to 1224' across top of Salt. Removed BOP. Spotted 10 sacks cement plug from 54' to surface. Installed dry hole marker and cleaned location. Will advise when location is ready for inspection.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>B. J. Barber</u>	TITLE <u>Area Engineer</u>	DATE <u>4-28-75</u>
APPROVED BY <u>John W. Runyan</u>	TITLE	DATE
CONDITIONS OF APPROVAL, IF ANY:		