

NEW MEXICO OIL CONSERVATION COMMISSION

MAY 10 1937

Santa Fe, New Mexico

DUPLICATE

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Gulf Oil Corporation

Tulsa, Oklahoma

Company or Operator

Address

Willie A. Weir B

Well No. 1

NW SE

of Sec. 26

T. 19S

R. 36E

Lease

N. M. P. M.

Monument

Field

Lea

County

Well is 660 feet south of the North line and 1200 feet west of the East line of NW SE

If State land the oil and gas lease is No.

Assignment No.

If patented land the owner is

Address

If Government land the permittee is

Address

The Lessee is

Gulf Oil Corporation

Address

Tulsa, Oklahoma

Drilling commenced January 19, 1937

Drilling was completed

February 9, 1937

Name of drilling contractor

Loffland Brothers

Address

Tulsa, Oklahoma

Elevation above sea level at top of casing 5072 feet

The information given is to be kept confidential until

?

19

OIL SANDS OR ZONES

No. 1, from 5990' to 5995'

No. 4, from

to

No. 2, from Pay 5880'

No. 5, from

to

No. 3, from

No. 6, from

to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from Rotary Hole to

feet.

No. 2, from

feet.

No. 3, from

feet.

No. 4, from

feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
10-5/4	52.75	8	Lapw.	277'				
7-5/8	22	8	Lapw.	1189				
5-1/2	17	10	Lapw.	5789				

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
13-5/4"	10-5/4	277	200	Halliburton		
9-7/8	7-5/8	1189	200	"		
6-5/4	5-1/2	5789	175	"		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		Hydrochloric Acid	2,000	2-11-37	5995'	
		"	5,000	2-13-37	5995'	

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 5995' feet, and from feet to feet

Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing March 1, 1937

The production of the first 24 hours was 186 barrels of fluid of which % was oil; %

emulsion; % water; and % sediment. Gravity, Be.

If gas well, cu. ft. per 24 hours 800,000 Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

EMPLOYEES

Driller Driller

Driller Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 6th

Tulsa, Oklahoma

May 6, 1937

day of May, 1937

Name

H. A. Bader

Position

General Superintendent

Representing

Gulf Oil Corporation

Company or Operator

My Commission expires March 10, 1940

Address

Tulsa, Oklahoma

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0'	59'		Surface sand & shells
	230		Shells & Caliche
	390		Red bed
	450		Sand & shells
	667		Red bed
	857		Red bed & shells
	1065		Red bed
	1278		Anhydrite
	2485		Salt & shells
	2554		Shells
	2622		Anhydrite & Salt
	2684		Anhydrite & gyp
	2794		Anhydrite
	2859		Anhydrite & lime
	2966		Lime & Anhydrite
	3051		Broken lime, Anhydrite
	3110		Lime, broken
	3190		Anhydrite & lime
	3271		Lime & gyp
	3659		Lime
	3704		Broken lime, showing gas
	3726		Hard lime
	3783		Sandy lime
	3833		Lime
	3905		Lime
	3995'		TOTAL DEPTH
Formation Tops:			
		Anhydrite	1165'
		Salt Top	1275
		Salt Base	2485
		Brown lime	2800
		Upper San Andres	3990
		Pay	3880