

Submit 3 Copies To Appropriate District Office

District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103

Revised March 25, 1999

WELL API NO.

30-025-04093

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

015264

7. Lease Name or Unit Agreement Name:

Northwest Eumont Unit

8. Well No. #148

9. Pool name or Wildcat

Eumont Yates

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator Rhombus Operating Co., Ltd.

3. Address of Operator

P.O. Box 8316, Midland, Texas 79708-8316

4. Well Location

Unit Letter M : 660 feet from the South line and 990 feet from the West line

Section 27

Township 19-S

Range 36-E

NMPM

County Lea

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3,700' GL

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Surface casing: 8-5/8" @ 346', cmt'd circulated
Openhole: 4,019 - 4,100'

Production csg: 5 1/2" 14-15.50#, TOC 2,675' by T.S.
Tubing/packer: Rice Duo-line tbg w/ Baker 45-B AD pkr @ 3,991'

1. Dig & line earthen work pit, flow well down as needed. MIRU. NU BOP.
2. POOH laying down injection tubing and packer.
3. RIH w/ tbg to 4,010' and circulate hole w/ mud, pump 25 sx C cmt w/ 2% CaCl₂ @ 4,010'. WOC & TAG.
4. POOH w/ tbg to 2,800' and pump 25 sx C cmt 2,800 - 2,700'. **base of salt plug**
5. RIH w/ wireline and perforate casing @ 1,500'.
6. RIH w/ AD-1 packer to 1,300' and squeeze 35 sx C cmt 1,500 - 1,400'. **top of salt plug**
7. RIH w/ wireline and perforate casing @ 396'.
8. POOH w/ AD-1 packer to 200' and squeeze 50 sx C cmt 396 - 296'. WOC & TAG **surface casing shoe plug**
9. Pump 10 sx C cmt 50' to surface. **surface plug**
10. Cut off wellhead and install dryhole marker. Cut off anchors and level location.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE Engineer

DATE 09/06/02

Type or print name

James F. Newman, P.E.

Triple N Services, Inc.

Telephone No. 915-687-1994

(This space for State ORIGINAL SIGNED BY

GARY W. WINK

APPROVED BY

OC FIELD REPRESENTATIVE II/STAFF MANAGER

Conditions of approval, if any:

THE COMMISSION MUST BE NOTIFIED 24 HOURS PRIOR TO THE BEGINNING OF

PLUGGING OPERATIONS FOR THE C-103

TO BE APPROVED.

SEP 11 2002