NUMBER OF COPIE	S RECEIVED	
015	TRIBUTION	
SANTA FF		
FILE		
U.S.G.S.		··
LAND OFFICE		,
TRANSPORTER	OIL	
	GAS	1
PRORATION OFFI	E	
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

MISCELLANEOUS NOTICES

onal instructions in the Rules and	Indicate Nature of Notice by Checking	Below	
OTIGE OF INTENTION CHANGE PLANS	Notice of Intention to Temporarily Abandon Well	Notice of Intention to Drill Deeper	
OTICE OF INTENTION	Notice of Intention	Notice of Intention	
PLUG WELL	TO PLUG BACK	TO SET LINER	
tice of Intention Squeeze	Notice of Intention to Acidize	Notice of Intention	
		то Sисот (Nitro)	
GUN PERFORATE	NOTICE OF INTENTION (OTHER) SAND FRACTURE X	Notice of Intention (Other)	
CONSERVATION COMMISS	TON	, , , , , , , , , , , , , , , , , , ,	· · · · · · · · · · · · · · · · · · ·
TA FE, NEW MEXICO	HOBBS, NEW MEX	ICO OCTOBER 6	, 1961
	(Place)	(Date)	
lemen:			
Following is a Notice of Intention	on to do certain work as described below at the		••••••
BLAIR ST	PEELE J. A. FOSTER	Well No	J
(Company or	33 , T. 19 , R. 36 , NMP	FILMONT	(Unit)
(40-acre Subdivision)	, T, R, NMP	м.,	Po
(FC L PUMP, RODS AND PACKER AND 3" FR K UP DOWELL AND F EFINED GRUDE AND	AGTURE TUBING. PRACTURE ZONE PERFORATED 398 40,000# 20-40 SAND.	REGULATIONS)) OAL
(FC L PUMP, RODS AND PACKER AND 3" FR K UP DOWELL AND F EPINED GRUDE AND T FOR INGREASE IN LL OUT PLUG @ 403 ULTS OF PRODUCTION NEGESSARY PERFORA EFINED GRUDE AND T FOR INGREASE IN	FULL DETAILS OF PROPOSED PLAN DLLOW INSTRUCTIONS IN THE RULES AND 2" TUBING. PACTURE TUBING. PACTURE ZONE PERFORATED 398 40,000# 20-40 SAND. PRODUCTION: O' AND TEST ZONE PERFORATED IN TEST WILL DETERMINE NEED TEST ZONE 4119'-4158' WILL IN TES	PREGULATIONS) 39'-4001' WITH 20,000 4119'-4158' FOR OIL OF FURTHER TREATMENT BE FRACTURED WITH 20.	. PRODU
(FC) L PUMP, RODS AND PACKER AND 3" FR K UP DOWELL AND F EFINED GRUDE AND IT FOR INCREASE IN LL OUT PLUG @ 403 ULTS OF PRODUCTION NEGESSARY PERFORM EFINED GRUDE AND	FULL DETAILS OF PROPOSED PLAN DLLOW INSTRUCTIONS IN THE RULES AND 2" TUBING. PACTURE TUBING. PACTURE ZONE PERFORATED 398 40,000# 20-40 SAND. PRODUCTION: O' AND TEST ZONE PERFORATED IN TEST WILL DETERMINE NEED TEST ZONE 4119'-4158' WILL IN TES	PREGULATIONS) 39'-4001' WITH 20,000 4119'-4158' FOR OIL OF FURTHER TREATMENT BE FRACTURED WITH 20.	. PRODUC
(FO L PUMP, RODS AND PACKER AND 3" FR EK UP DOWELL AND F EFINED GRUDE AND IT FOR INCREASE IN LL OUT PLUG @ 403 BULTS OF PRODUCTION NECESSARY PERFORA EFINED GRUDE AND IT FOR INCREASE IN TUBING, PUMP AND	FULL DETAILS OF PROPOSED PLAN DLLOW INSTRUCTIONS IN THE RULES AND THE TUBING. PACTURE TUBING. PACTURE ZONE PERFORATED 398 40,000# 20-40 SAND. PRODUCTION. O' AND TEST ZONE PERFORATED TEST WILL DETERMINE NEED TEST ZONE 4119'-4158' WILL IN 1900 AND	PREGULATIONS) 39'-4001' WITH 20,000 4119'-4158' FOR OIL OF FURTHER TREATMENT BE FRACTURED WITH 20.	. PRODUC
(FO L PUMP, RODS AND PACKER AND 3" FR EK UP DOWELL AND F EFINED GRUDE AND IT FOR INCREASE IN LL OUT PLUG @ 403 BULTS OF PRODUCTION NECESSARY PERFORA EFINED GRUDE AND IT FOR INCREASE IN TUBING, PUMP AND	FULL DETAILS OF PROPOSED PLAN DILLOW INSTRUCTIONS IN THE RULES AND TUBING. RACTURE TUBING. RACTURE ZONE PERFORATED 398 40,000# 20-40 SAND. PRODUCTION: O' AND TEST ZONE PERFORATED IN TEST WILL DETERMINE NEED TED ZONE 4119'-4158' WILL IN 40,000# 20-40 SAND. I PRODUCTION. I PRODUCTION. I PRODUCTION.	REGULATIONS) 39'-4001' WITH 20,000 4119'-4158' FOR OIL OF FURTHER TREATMENT BE FRACTURED WITH 20,	. PRODUC
(FO L PUMP, RODS AND PACKER AND 3" FR K UP DOWELL AND F EPINED GRUDE AND T FOR INGREASE IN LL OUT PLUG @ 403 ULTS OF PRODUCTION NEGESSARY PERFORA EPINED GRUDE AND T FOR INGREASE IN TUBING, PUMP AND	FULL DETAILS OF PROPOSED PLAN DILLOW INSTRUCTIONS IN THE RULES AND 2" TUBING. RACTURE TUBING. RACTURE ZONE PERFORATED 398 40,000# 20-40 SAND. PRODUCTION. NO AND TEST ZONE PERFORATED N TEST WILL DETERMINE NEED TED ZONE 4119'-4158' WILL IN 40,000# 20-40 SAND. PRODUCTION. RODS. By	REGULATIONS) 39'-4001' WITH 20,000 4119'-4 58' FOR OIL OF FURTHER TREATMENT BE FRACTURED WITH 20,	. PRODU
L PUMP, RODS AND PACKER AND 3" FR K UP DOWELL AND F EFINED GRUDE AND T FOR INCREASE IN LL OUT PLUG Q 403 ULTS OF PRODUCTION NECESSARY PERFORA EFINED GRUDE AND T FOR INCREASE IN TUBING, PUMP AND	FULL DETAILS OF PROPOSED PLAN DILLOW INSTRUCTIONS IN THE RULES AND 2" TUBING. RACTURE TUBING. RACTURE ZONE PERFORATED 398 40,000# 20-40 SAND. PRODUCTION. O' AND TEST ZONE PERFORATED IN TEST WILL DETERMINE NEED TED ZONE 4119'-4158' WILL IN 40,000# 20-40 SAND. I PRODUCTION. RODS. By	REGULATIONS) 39'-4001' WITH 20,000 4119'-4 58' FOR OIL OF FURTHER TREATMENT BE FRACTURED WITH 20,	. PRODU
(FO L PUMP, RODS AND I PACKER AND 3" FR OK UP DOWELL AND F EFINED GRUDE AND IT FOR INCREASE IN LL OUT PLUG @ 403 BULTS OF PRODUCTION NEGESSARY PERFORA EFINED GRUDE AND IT FOR INCREASE IN I TUBING, PUMP AND	FULL DETAILS OF PROPOSED PLAN DILLOW INSTRUCTIONS IN THE RULES AND 2" TUBING. RACTURE TUBING. RACTURE ZONE PERFORATED 398 40,000# 20-40 SAND. PRODUCTION. O' AND TEST ZONE PERFORATED IN TEST WILL DETERMINE NEED ITED ZONE 4119'-4158' WILL IN 40,000# 20-40 SAND. I PRODUCTION. RODS. Position	REGULATIONS) 39'-4001' WITH 20,000 4119'-4 58' FOR OIL OF FURTHER TREATMENT DE FRACTURED WITH 20, Company or Operator JOE A. COLLIAN JOENT	. PRODU