NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

| | Indicate Nature of Report by Checking | Below |
|--|---|---|
| REPORT ON BEGINNING DRILLING OPERATIONS | REPORT ON RESULT OF TEST | REPORT ON REPAIRING WELL |
| REPORT ON RESULT OF PLUGGING WELL | REPORT ON RECOMPLETION OPERATION | REPORT ON (Other) |
| | December 13, 1950 | Hobbs, New Mexice |
| Following is a report on the work | done and the results obtained under the heading | g noted above at the |
| Shell Oil Company | | Fost, er (Lease) |
| Velma Petroleum Com (Contractor | Deny , Well No4 | (Lease) in the SW 1/4 SW 1/4 of Sec. 34 |
| T. 19-3, R. 36-E, NMPM., | Euront Pool, | Lea County |
| The Dates of this work were as folows: | December 9, 19 | 254 |
| and approval of the proposed plan fue | | (Cross out incorrect words) , 19 |
| | LED ACCOUNT OF WORK DONE AND RES | |
| Ran 293 of 8-5/8" | | 300 sacks regular cement. |
| Ran 293° of 8-5/8° of Circulated out an es | LED ACCOUNT OF WORK DONE AND RES | 300 sacks regular cement. 4 hours tested casing with |
| Ran 293 of 8-5/8 c Circulated out an es | LED ACCOUNT OF WORK DONE AND RES casing and cemented at 306° with ctimated 100 sacks. After WOC 2 | 300 sacks regular cement. 4 hours tested casing with |
| Ran 293 of 8-5/8 c Circulated out an es | casing and cemented at 306° with stimated 100 sacks. After WOC 2 ates before drilling plug. Test for 30 minutes. Test OK. | 300 sacks regular cement. 4 hours tested casing with |
| Ran 293 of 8-5/8 c Circulated out an explose for 30 minutes of the common state of th | casing and cemented at 306° with timated 100 sacks. After WOC 20 tes before drilling plug. Test for 30 minutes. Test OK. Shell Oil Company | 24 hours tested casing with OK. Drilled plug and tested Drilling Foreman (Title) |
| Ran 293 of 8-5/8 Circulated out an establishment with 250 psi Witnessed by B. L. Simmers (Name) | casing and cemented at 306' with stimated 100 sacks. After WOC 2 ates before drilling plug. Test for 30 minutes. Test OK. Shell Oil Company OMMISSION I hereby certify to the best of my Name | A hours tested casing with OK. Drilled plug and tested Drilling Foreman (Title) hat the information given above is true and complete knowledge. Original signed by |