

DUPLICATE

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

RECEIVED
DEC 14 1949
HOBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	X
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

July 5, 1945

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the Amerada Petroleum Corporation W.A. Weir Well No. 3 in the

Company or Operator W.A. Weir Lease 35 of Sec. 35, T. 19, R. 34, N. M. P. M.,
Field, Monument Lea County.

The dates of this work were as follows: June 23, 1949

Notice of intention to do the work was (~~submitted~~) submitted on Form C-102 on June 23, 19 49
and approval of the proposed plan was (~~submitted~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

3945' Total Depth. 6-5/8" OD Casing set at 3815'.

Rigged up Rotary Tool and reamed open hole from 3815' to 3945'. Rigged up and ran Lane-Wells Gamma Ray & Neutron Surveys. Circulated hole clean and ran back in hole with tubing & packer. Swabbed well in and in eight hours, flowed 24.90 bbls. fluid, avg. 17% water. GOR 4340. Acidised well with 5000 gals. of Dowell 22% L.T. Acid with 200# pump Pressure. Swabbed well in and put on 1/2" choke. In 24 hours well flowed 112.92 bbls fluid, 3% Water. GOR 3290. Work-over complete.

Witnessed by D.F. Furse Amerada Petroleum Corporation Foreman
Name Company Title

Subscribed and sworn before me this

I hereby swear or affirm that the information given above is true and correct.

13 day of Dec. 19 49
[Signature]
Notary Public

Name [Signature]
Position Assistant District Superintendent
Representing Amerada Petroleum Corporation
Company or Operator

My commission expires 10/24/53

Address Drawer "D", Monument, New Mexico

Remarks:

APPROVED

DEC 14 1949
Date

[Signature]
OIL & GAS INSPECTOR

Title

