

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	18	18	Cellar and sub structure.
18	90	72	Surface sand and Caliche.
90	120	30	Red rock and Red Bed.
120	200	80	Red Bed. (Set 121 Csg. at 217' W/450 sacks.)
200	235	35	Red Rock.
235	329	94	Red Rock.
329	335	6	Shells.
335	514	179	Red Bed.
514	752	238	Red Bed and shells.
752	980	228	Red Rock.
980	1000	20	Red Bed.
1000	1104	104	Red Bed Gyp, Shells. (Top of Anhydrite 1090)
1104	1108	4	Anhydrite.
1108	1224	116	Anhydrite.
1224	1285	61	Salt.
1285	1325	40	Salt and Anhydrite and Shells.
1325	1435	110	Salt.
1435	1504	69	Salt, Anhydrite, and shells.
1504	2055	551	Salt.
2055	2230	175	Salt and shells.
2230	2245	15	Anhydrite.
2245	2268	23	Salt.
2268	2350	82	Salt.
2350	2380	30	Salt and Anhydrite. (Base Salt.)
2380	2412	32	Anhydrite.
2412	2440	28	Anhydrite. (set 8 5/8" Csg. at 2425' W/500 sacks.)
2440	2470	30	Anhydrite and streaks of salt.
2470	2541	71	Anhydrite.
2541	2804	263	Anhydrite. (Top of Main Line. 2700')
2804	2844	40	Gray and Brown Line and Anhydrite.
2844	2943	99	Lime.
2943	2993	50	Broken Line.
2993	3352	359	Lime.
3352	3386	34	Gray Line.
3386	3544	42	Lime. (Gas showing at 3492-3535)
3544	3603	59	Sandy Lime.
3603	3857	254	Lime. (set 6-5/8" Csg. at 3815' W/100 sacks.)
3857	3864	7	Crystal Lime. (Top pay 3825')
3864	3881	17	Brown Line. (Show of gas) increase in pay 3870-80.
3881	3885	4	Brown Line and streaks of lime.
3885	3933	48	Lime. (Increase in pay 3812'-20')
3933	3945	12	Lime (Total Depth.)
			Acidized with 1000 Gal acid 4/21/36.
			CASING RECORD
			MUDLOG AND CEMENTING RECORD
			RECORD OF DRILLING AND SPECIAL TESTS
			TOOLS USED
			PRODUCTION
			EMPLOYEES
			FORMATION RECORD OF OTHER SITES