

OIL CONSERVATION DIVISION

P.O. BOX 2088

SUNNYvale, NEW MEXICO 87501

Form O-103
Revised 10-1-73

NO. OF COPIES RECEIVED	
DATE RECEIVED	
DATE PAID	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Free <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT TO DRILL" (FORM O-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Amerada Hess Corporation	8. Farm or Lease Name W. A. Weir
3. Address of Operator Drawer D, Monument, New Mexico 88265	9. Well No. 6
4. Location of Well UNIT LETTER <u>C</u> <u>660</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM THE <u>West</u> LINE, SECTION <u>35</u> TOWNSHIP <u>19-S</u> RANGE <u>36-E</u> N.M.P.M.	10. Field and Pool, or Wildcat Eunice Monument G/SA
15. Elevation (Show whether DF, RT, GR, etc.) 3652' DF	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input checked="" type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

November 14, 1979

Pulled rods, pump & tbg., Ran 4-1/8" bit on 2-3/8" tbg. to clean scale fr. 5" liner. Checked top of fill inside 5" liner at 3939'. Cleaned out fill w/3-1/8" bailer to 3948'. Acidized Grayburg San Andres zone thru 5" liner perf. fr. 3842' to 3948' w/6100 gal. 20% NE FE acid w/additives in three stages. Flushed w/2% KCl water. Swabbed load. Re-ran prod. equipment and resumed pumping.

Test of 12-1-79: Pumped 12 b.o. & 8 b.w. in 24 hrs. on 9-54" SPM.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>EB Fisher</u>	TITLE <u>Supv. Adm. Ser.</u>	DATE <u>12-18-79</u>
APPROVED BY <u>John S. Smith</u>	TITLE <u></u>	DATE <u>DEC 21 1979</u>

CONDITIONS OF APPROVAL, IF ANY: