

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOBBS OFFICE OCC

MISCELLANEOUS REPORTS ON WELLS

1955 MAR 7 PM 3:30

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON REPAIRING WELL	X
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other) SAND-OIL FRAC	X

March 3, 1955

(Date)

Monument, New Mexico

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum Corporation

(Company or Operator)

W.A. Weir

(Lease)

J.P. (Bum) Gibbins

(Contractor)

Well No. 8 in the NW 1/4 NW 1/4 of Sec. 35

T. 19-S, R. 36-E, NMPM, Monument Pool, Lea County.

The Dates of this work were as follows: January 29, 1955 to February 9, 1955, incl.

Notice of intention to do the work (was) ~~submit~~ submitted on Form C-102 on January 31, 1955, (Cross out incorrect words)

and approval of the proposed plan (was) ~~submit~~ obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

3960' T.D.

Pulled tubing and packer. Ran Lane Wells gamma ray and neutron surveys. Found 6-5/8" OD casing leak above 2487'. Repaired 6-5/8" OD casing by cutting off casing at 2487' and pulling. Ran 82 joints of 6-5/8" OD casing which was spliced at 2487' with a Baash-Ross casing bowl. Tested 6-5/8" OD casing with 2000# for 1/2 hour - held OK.

Sand-oiled 5-7/8" open hole from 3845' to 3960' with 20,000 gallons of Famariss 24 gravity oil and 20,000 pounds of sand. Ran 2-7/8" OD WUE tubing and Gulberson KV-30 packer. Put well to flowing 2-9-55.

2-12-55 - Flowed 26 barrels of oil and 25 barrels of water in 12 hours on 13/64" choke; TP 650#; gas volume 940,940 cfpd; GOR 36,190.

Witnessed by E. E. Shirley Amerada Petroleum Corporation Farm Boss
(Name) (Company) (Title)

Approved: OIL CONSERVATION COMMISSION

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name: W.A. Weir

Position: Foreman

Representing: Amerada Petroleum Corporation

Address: Drawer D Monument, New Mexico

(Title)

(Date)