



NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

RECEIVED 4 PM 1:47  
WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

AREA 640 ACRES  
LOCATE WELL CORRECTLY

SINCLAIR OIL & GAS COMPANY  
(Company or Operator)

SKLEY HAVERTY  
(Lease)

Well No. **1-A1**, in **SE 1/4** of **SW 1/4**, of Sec. **35**, T. **19S**, R. **36E**, NMPM.  
**Burnee Monument (Monument Area)** Pool, **Lee** County.  
Well is **950** feet from **South** line and **2310** feet from **West** line  
of Section **35**. If State Land the Oil and Gas Lease No. is \_\_\_\_\_  
Drilling Commenced **10/30/**, 19 **59** Drilling was Completed **11/11/**, 19 **59**  
Name of Drilling Contractor **Moran Drilling Company**  
Address **Hobbs, New Mexico**  
Elevation above sea level at Top of Tubing Head **3,604**. The information given is to be kept confidential until \_\_\_\_\_, 19 \_\_\_\_\_.

OIL SANDS OR ZONES

No. 1, from **3620** to **3900** No. 4, from \_\_\_\_\_ to \_\_\_\_\_  
No. 2, from \_\_\_\_\_ to \_\_\_\_\_ No. 5, from \_\_\_\_\_ to \_\_\_\_\_  
No. 3, from \_\_\_\_\_ to \_\_\_\_\_ No. 6, from \_\_\_\_\_ to \_\_\_\_\_

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from \_\_\_\_\_ to \_\_\_\_\_ feet.  
No. 2, from \_\_\_\_\_ to \_\_\_\_\_ feet.  
No. 3, from \_\_\_\_\_ to \_\_\_\_\_ feet.  
No. 4, from \_\_\_\_\_ to \_\_\_\_\_ feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
7-5/8"OD	23	New	308				Surface
2-7/8"OD	6.60	New	3048			3873 - 3885	Production

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
11"	7-5/8"	308'	300	Halliburton		
6-3/4"	2-7/8"	3,948'	167	"		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Treated perforations from 3873'-3885' with 500 gallons mud acid, 1000 gallons regular acid and a 5000 gallon, 5000# sand-oil free treatment.

Result of Production Stimulation **Well flowed 44 bbls. of 32 gravity oil in 4 hours.**

Depth Cleaned Out \_\_\_\_\_

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from Surface feet to 3,950 feet, and from feet to feet.  
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing November 8, 1959  
OIL WELL: The production during the first 24 hours was 264 barrels of liquid of which 100% was oil; 0% was emulsion; 0% water; and 0% was sediment. A.P.I. Gravity 32°  
GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.  
Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy.	1040'	T. Devonian	
T. Salt	1135'	T. Silurian	
B. Salt	2390'	T. Montoya	
T. Yates	2483'	T. Simpson	
T. 7 Rivers	2760'	T. McKee	
T. Queen	3,278'	T. Ellenburger	
T. Grayburg	3,620'	T. Gr. Wash.	
T. San Andres		T. Granite	
T. Glorieta		T.	
T. Drinkard		T.	
T. Tubbs		T.	
T. Abo		T.	
T. Penn.		T.	
T. Miss.		T.	
T. Ojo Alamo			
T. Kirtland-Fruitland			
T. Farmington			
T. Pictured Cliffs			
T. Menefee			
T. Point Lookout			
T. Mancos			
T. Dakota			
T. Morrison			
T. Penn.			
T.			

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	40	40	Sand and caliche				
40	1040	1000	Red beds				
1040	1135	95	Anhydrite				
1135	2390	1255	Salt and anhydrite				
2390	2942	552	Anhydrite & gypsum				
2942	3010	68	Lime and anhydrite				
3010	3950	940	Lime				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Company or Operator Sinclair Oil & Gas Company Address 520 East Broadway, Hobbs, N. M.  
Name C. C. Salter Position or Title District Superintendent  
12/1/59