

District I
PO Box 1980, Hobbs, NM 88241-1980
District II
PO Drawer DD, Artesia, NM 88211-0719
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
PO Box 2088, Santa Fe, NM 87504-2088

State of New Mexico
Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION
PO Box 2088
Santa Fe, NM 87504-2088

Form C-101
Revised February 10, 1994

Instructions on back
Submit to Appropriate District Office
State Lease - 6 Copies
Fee Lease - 5 Copies

☐ AMENDED REPORT

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

Operator Name and Address. Amerada Hess Corporation Drawer D Monument, New Mexico 88265		OGRID Number 000495
Property Code 000162	Property Name J. R. Phillips <i>Gas Com</i>	API Number 30 - 025-04130
		Well No. 1

⁷ Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
A	1	20S	36E		330	North	330	East	Lea

⁸ Proposed Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
⁹ Proposed Pool 1 <i>Eumont 4-SR-2A</i>					¹⁰ Proposed Pool 2				

¹¹ Work Type Code P	¹² Well Type Code	¹³ Cable/Rotary	¹⁴ Lease Type Code P	¹⁵ Ground Level Elevation 3586' KB
¹⁶ Multiple	¹⁷ Proposed Depth	¹⁸ Formation Eumont Yates 7RQ	¹⁹ Contractor	²⁰ Spud Date

²¹ Proposed Casing and Cement Program

Hole Size	Casing Size	Casing weight/foot	Setting Depth	Sacks of Cement	Estimated TOC
	12-1/2"	40#	202'	Csg. ran	in 1936.
	9-5/8"	36#	2274'	" "	" "
	7"	24#	3795'	" "	" "

²² Describe the proposed program. If this application is to DEEPEN or PLUG BACK give the data on the present productive zone and proposed new productive zone. Describe the blowout prevention program, if any. Use additional sheets if necessary.

Well currently TA'd in Grayburg San Andres Zone with CIBP set at 3431'.

Plan to MIRU pulling unit, remove wellhead & install BOP. *USL-3340-A<SD>* TIH w/CBL/VDL/CCL/GR & 16g fr. 3431' to TOC. Check bond across Eumont interval. Shoot holes & circ. cement to surface. TIH w/7" pkr. set at 3420' & test CIBP to 4000 PSI. TIH w/4" perf. gun & perf. 7" csg. in Eumont Zone w/2SPF at following intervals: 3072' - 3084', 3100' - 3110', 3126' - 3132', 3150' - 3160', 3208' - 3304', & fr. 3316' - 3324'. Acidize Eumont perfs. w/7100 gal. 15% NEFE DI HCL acid. CONTINUED ATTACHED.

²³ I hereby certify that the information given above is true and complete to the best of my knowledge and belief.

Signature: *R. L. Wheeler, Jr.*

Printed name:

R. L. Wheeler, Jr.

Title:

Admin. Svc. Coord.

Date:

6-5-96

Phone:

505 393-2144

OIL CONSERVATION DIVISION

Approved by:

ORIGINAL

Title:

DISTRICT SUPERVISOR

Approval Date:

JUN 17 1996

Expiration Date:

Conditions of Approval:

Attached ☐

Permit Expires 1 Year From Approval
Date Unless Drilling Underway