

DUPLICATE

# OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

RECEIVED  
JUL 7 1948  
FORMS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	X
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

July 5, 1948

Date

Monument, New Mexico

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the  
Amerada Petroleum Corporation J. R. Phillips Well No. 1 in the  
Company or Operator Lease  
NE 1/4 NE 1/4 of Sec. 1, T. 20S, R. 36E, N. M. P. M.,  
Monument Field, Lea County.

The dates of this work were as follows: July 1 - 5, 1948

Notice of intention to do the work was (~~submitted~~) submitted on Form C-102 on June 22, 1948  
and approval of the proposed plan was (~~obtained~~) obtained. (Cross out incorrect words.)

### DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

3900' Total Depth, Lime. Ran Dowell Spinner Survey and pumped in 27 1/2 bbls. water in 15 minutes @ 950# pressure. Most of water went in at 3795'-3815', 54 1/2, 48GPM and at 3835'-3850', 35 1/2, 30 1/2 GPM. Plugged well back to 3889' with 34 gallons Dowell K-70 & K-71 Plastic, no filler. Used 950# pressure, got 11' fill, 18 gallons plastic went into formation. Finished 8:30AM, 7-2-48. Ran Guiberson Hookwall Packer and 122 jts. 2-7/8" OD, EUE, 6.5#, R-2, 8-RT & 10-VT, SS Tubing SH with 2-4' subs in string and Dowell Seating Nipple on bottom. Displaced water with 180 bbls. oil and set packer at 3780' with bottom of tbg. at 3885'. Tested packer, left 500# on casing, pulled swab 5 times and well kicked off. In 24 hrs. to 7:00AM, 7-5-48, flowed 345.86 bbls. oil, 2% water, 3/8"-1 1/2" choke, gas 94M, GOR 272, GOR 278. Workover complete.

Witnessed by K. V. Stephenson

Name Amerada Pet. Corp. Company

Foreman

Title

Subscribed and sworn before me this

5th day of July 1948

I hereby swear or affirm that the information given above is true and correct.

Name

Position

Representing

Aest. Dist. Supt.

Amerada Petroleum Corporation  
Company or Operator

My commission expires

Address

Drawer D, Monument, New Mexico

Remarks:

Proy. Yankrough  
Title

APPROVED

JUL 7 1948

1942-1943

1944-1945

1946-1947

1948-1949

1950-1951

1952-1953

1954-1955

1956-1957

1958-1959

1960-1961

1962-1963

1964-1965

1966-1967

1968-1969

1970-1971

1972-1973

1974-1975

1976-1977

1978-1979

1980-1981

1982-1983

1984-1985

1986-1987

1988-1989

1990-1991

1992-1993

1994-1995

1996-1997

1998-1999

2000-2001

2002-2003

2004-2005

2006-2007

2008-2009

2010-2011

2012-2013

2014-2015

2016-2017

2018-2019

2020-2021

1942-1943

1942-1943

1942-1943