## NI I VICO OIL CONSERVATION C I SION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature	or report by ence		
REPORT ON BEGINNING DRILLING OPERATIONS	REPO	RT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL	REPO	RT ON PULLING OR OTHE	RWISE
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		RT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			<u> </u>
Mamoment,		April :	16, 1937
OIL CONSERVATION COMMISSION, SANTA FE, NEW MEXICO.	Place		Date
Gentlemen:			
Following is a report on the work done and the resu	ılts obtained unde	r the heading noted above	e at the
Amerada Petrolaum Corporation	Phil	lips Well No.	
Company or Operator  of Sec.	Lease , T <b>20</b>		
Monumen Field.		, It	, N. M. P. M.,
the dates of this work were as follows:			County.
otice of intention to do the work was <del>{ was not }</del> su			
5-1/2" 17# 10-Thd. New Seamless can the Halliburton Method with 100 sach	sing was set	in this well at 382	22° and cemented
5-1/2" 17# 10-Thd. New Seamless case the Halliburton Method with 100 sach Casing and fittings were tested with undisturbed for thirty minutes. No drilled out of the casing and the as and allowed to stand undisturbed for the drilling was then resumed.	ks. h 1200; pump drop in pres ame test of li	pressure and ellowe sure resulted so the	d to stand B coment was the
Casing and fittings were tested with undisturbed for thirty minutes. No drilled out of the casing and the sa and allowed to stand undisturbed for	ks. h 1200; pump drop in pres ame test of li	pressure and ellowe sure resulted so the	d to stand B coment was the
Casing and fittings were tested with undisturbed for thirty minutes. No drilled out of the casing and the sa and allowed to stand undisturbed for the drilling was then resumed.	ks. h 1200; pump drop in pres ame test of li	pressure and ellowersure resulted so the 200# pump pressure tes. No droppin pressure	d to stand B coment was the
Casing and fittings were tested with undisturbed for thirty minutes. No drilled out of the casing and the as and allowed to stand undisturbed for the drilling was then resumed.  Sitnessed by Claud Cook  Name	h 1200; pump drop in presame test of lir thirty minu.  Noble Drilli Comp.	pressure and ellowersure resulted so the source pump pressure tes. No drop in page 201 APR	d to stand s coment was the was again applie was arriver resulted
Casing and fittings were tested with undisturbed for thirty minutes. No drilled out of the casing and the sa and allowed to stand undisturbed for the drilling was then resumed.  Subscribed and sworn before me this.	h 1200; pump drop in presame test of lirty minu.  Noble Drilli Compa	pressure and ellowersure resulted so the source pump pressure tes. No drop in page 201 APR	d to stand s coment was the was again applie was arriver resulted Tool-pusher
Casing and fittings were tested with undisturbed for thirty minutes. No drilled out of the casing and the sa and allowed to stand undisturbed for the drilling was then resumed.  Subscribed and sworn before me this	h 1200 pump drop in presame test of lirty minus  Noble Drilli Compa  I hereby swe is true and	pressure and ellowersure resulted so the 200% pump pressure tes. No droppin pressure tes. No droppin pressure tes. No droppin pressure tes. Tarket	d to stand s coment was the was again applie was arriver resulted
Casing and fittings were tested with undisturbed for thirty minutes. No drilled out of the casing and the sa and allowed to stand undisturbed for the drilling was then resumed.  Subscribed and sworn before me this.	h 1200; pump drop in present test of litre thirty minus  Noble Drillic Compa  I hereby swe is true and Name Position	pressure and allowersure resulted so the 200# pump pressure tes. No drop in parties. No drop in parties are infectively and the infection of the correct.	d to stand  B coment was the  Was again applie  ressure resulted  Tool-pusher  Pate  Organization given above
Casing and fittings were tested with undisturbed for thirty minutes. No drilled out of the casing and the as and allowed to stand undisturbed for the drilling was then resumed.  Subscribed and sworn before me this	h 1200 pump drop in presame test of lirty minus  Noble Drilli Compa  I hereby swe is true and	pressure and ellowersure resulted so the source resulted so the source resulted so the source resulted so the source results and the information of the source results and the information of the source results and the source results are results and the source results and the source results are results and the source results and the source results and the source results are results and the source results and the source results are results and the source results and the source results are results and the source results and the source results are	to stand to stand to coment was the was again applie to resulted  Tool-pusher  File  Ormation given above
Casing and fittings were tested with undisturbed for thirty minutes. No drilled out of the casing and the sa and allowed to stand undisturbed for the drilling was then resumed.  Subscribed and sworn before me this	h 1200; pump drop in presented test of 12 thirty minus  Noble Drillic Company  I hereby swe is true and Name Position Representing	pressure and allowersure resulted so the 200 pump pressure tes. No drop in parties. No drop in parties affirm that the information of the correct.  Superior and allowersure a	to stand to stand the company was the was again application resulted  Tool-pusher Paule  Ormation given above
Casing and fittings were tested with undisturbed for thirty minutes. No drilled cut of the casing and the sa and allowed to stand undisturbed for the drilling was then resumed.  Name  Subscribed and sworn before me this	h 1200; pump drop in presented test of 12 thirty minus  Noble Drillic Company  I hereby swe is true and Name Position Representing	pressure and ellowersure resulted so the source resulted so the source resulted so the source resulted so the source results and the information of the source results and the information of the source results and the source results are results and the source results and the source results are results and the source results and the source results and the source results are results and the source results and the source results are results and the source results and the source results are results and the source results and the source results are	to stand to stand the company was the was again application resulted  Tool-pusher Paule  Ormation given above