


**CONFIDENTIAL****OIL CONSERVATION COMMISSION**

Santa Fe, New Mexico

**MISCELLANEOUS REPORTS ON WELLS**

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on Re-perforating well	<b>X</b>

January 12, 1948

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.**CONFIDENTIAL**

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_  
Amerada Petroleum Corporation J. R. Phillips Well No. 5 in the \_\_\_\_\_  
 Company or Operator Lease  
NE 1/4 NE 1/4 of Sec. 1, T. 20S, R. 36E, N. M. P. M.,  
Monument Field, Lea County.

The dates of this work were as follows: January 8-12, 1948

Notice of intention to do the work ~~was~~ (was not) submitted on Form C-102 on \_\_\_\_\_ 19\_\_\_\_  
 and approval of the proposed plan ~~was~~ (was not) obtained. (Cross out incorrect words.)

**DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED**

5500' Plugged Back Depth. Killed well with mud, laid down 2-7/8" Hydril Tubing and perforated with Lane Wells from 5180' to 5200', 80 holes. Ran Gliberson Hook wall Packer and 167 joints of 2" EUE, 4.7#, J-55, R-2, 8-RT, SS Tubing New and displaced mud with 130 bbls. of oil. Set packer at 5183' with 1-3' perfs. sub on bottom of tubing at 5204'. Started swabbing 7:00PM, 1-9-48. Recovered 58.65 bbls. fluid, 6%BS&W and well kicked off at 1:30PM, 1-10-48. Put on 1/2" pos.choke at 2:30PM and in 17 1/2 hrs. flowed 68.31 bbls oil, 0%BS&W, gas 93M, GOR 993. In 24 hrs. to 7:00AM, 1-12-48, flowed 95.22 bbls. fluid, 4/10%BS&W, gas 70M, GOR 735, gravity 39.5 corrected.

Witnessed by D. F. Furse Amerada Petroleum Corporation Foreman  
 Name Company Title  
 Subscribed and sworn before me this \_\_\_\_\_  
12th. day of January, 19 48  
W. H. Taylor  
 Notary Public  
 My commission expires \_\_\_\_\_  
 I hereby swear or affirm that the information given above is true and correct.  
 Name Roy Yumbrough  
 Position Asst. Dist. Supt.  
 Representing Amerada Petroleum Corporation  
 Company or Operator  
 Address Drawer D, Monument, New Mexico

Remarks:

APPROVED

JAN 16 1948

Roy Yumbrough  
 Name  
 GAS INSPECTOR