


CONFIDENTIAL**OIL CONSERVATION COMMISSION**

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on Plugging Back	X

December 15, 1947

Date

Monument, New Mexico

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

CONFIDENTIAL

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____

Amerada Petroleum CorporationJ. R. PhillipsWell No. 5 in the _____

Company or Operator

Lease

NE 1/4 NE 1/4of Sec. 1T. 20SR. 36E

N. M. P. M.,

MonumentField, Lea

County.

The dates of this work were as follows: December 12 & 13, 1947.

Notice of intention to do the work was (~~was~~) submitted on Form C-102 on December 12, 1947
and approval of the proposed plan was (~~was~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

7227' Plugged back depth, went in hole with tubing and found top of plastic at 7227', cement with 50 sacks of Lone Star cement and finished at 3PM, went in hole at midnite and found top of cement at 6921', pulled up to 5833' and dumped 20 sacks lone star cement and pulled up to 5692' and reversed out approximately 2 sacks cement out of hole and pulled out of hole, let it set 12 hours and went in hole with tubing and found top of cement at 5697' and drilled out cement to 5722', gun perforated with Lane Wells with 4 holes at 5705' and tested with 1500# for 30 minutes and was OK and resumed perforating from 5660 to 5715' with 220 holes.

Witnessed by D. F. Furse Amerada Pet. Corp., Foreman
Name Company Title

Subscribed and sworn before me this _____

I hereby swear or affirm that the information given above is true and correct.

15 day of December, 19 47Name Roy YorkbroughPosition Asst Dist. Supt.Representing Amerada Pet. Corp.,
Company or Operator

My commission expires _____

Address Drawer D, Monument, New Mexi co.

Remarks:

APPROVEDDate DEC 19 1947

Roy Yorkbrough
OIL & GAS INSPECTOR
Name
Title