

CONFIDENTIAL**OIL CONSERVATION COMMISSION**

Santa Fe, New Mexico

DUPLICATE**MISCELLANEOUS REPORTS ON WELLS**

RECEIVED
DEC 16 1947
REGISTRY
HOBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on Plugging Back	X

SHEET #1

December 12, 1947

Date

Monument, New Mexico

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.**CONFIDENTIAL**

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum Corporation**J. R. Phillips**Well No. **5**

in the

Company or Operator

Lease

NE 1/4 NE 1/4of Sec. **1**T. **20S**R. **36E**

N. M. P. M.,

Monument

Field,

Lea

County.

The dates of this work were as follows:

December 9 - 12, 1947Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on **December 9,** 19**47**and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)**DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED**

7240' Retainer Depth, 7217' top of the plastic. Killed well with oil and ran Drill Stem Test with packer set at 7240'. Swabbed for 3 1/2 hrs. and recovered no fluid. Pulled Howco Tool and recovered 8' drlg. fluid. Set Baker Model K Cement Retainer rigged up as Bridging Plug at 7240', ran Dowell Seating Nipple and at 11:14 AM, 12-10-47, started Dowell Plastic down tubing. Plastic mixed 22 gallons clear and 33 gallons with filler. Started squeezing formation at 12 noon with 2200# to 3000# but plug would not go through nipple. Tried to reverse circulate with 4500# but could not move plug. Pulled tubing, ran steel line and found top of plastic at 7234'. Started dumping plastic with bailer and dumped 20 gals. to 7:20 PM. (Cont'd on Sheet #2)

Witnessed by **W. D. Jarred****Amerada Petroleum Corporation Farm Boss**

Name

Company

Title

Subscribed and sworn before me this

I hereby swear or affirm that the information given above is true and correct.

12th. day of **December**, 19**47**

Name

Position

Asst. Dist. Supt.

Representing

Amerada Petroleum Corporation
Company or Operator

My commission expires

My Commission Expires May 5, 1948

Address

Drawer D, Monument, New Mexico

Remarks:

APPROVEDDate **DEC 16 1947**

Roy Yarbrough
 Name
OIL & GAS
 Title