


CONFIDENTIAL

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

DUPLICATE
MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on Squeezing Well	X

November 29, 1947

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the
Amerada Petroleum Corporation **J. R. Phillips** Well No. **5** in the
 Company or Operator Lease

NE 1/4 NE 1/4 of Sec. **1**, T. **20S**, R. **36E**, N. M. P. M.,
Monument Field, **Lea** County.

The dates of this work were as follows: **November 27, 28, 29, 1947**

Notice of intention to do the work was (~~submitted~~) submitted on Form C-102 on **November 27**, 19 **47**
 and approval of the proposed plan was (~~received~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

7164' Drilled Out Depth. Ran tubing and Baker Model K Cement Retainer, displaced mud with water and set Retainer at 7055'. Pumped 98 sacks of regular cement into formation, maximum pressure 4000#. Drilled cement out from 7055' to 7164'. Ran Drill Stem Test and swabbed to test squeeze and recovered no fluid, no gas. Perforated with Lane Wells from 7110' to 7164', 324 holes. Ran back in hole with American Packer and 2-7/8" OD Tubing and left Packer swinging.

Witnessed by **D. F. Furse** **Amerada Petroleum Corporation** **Foreman**
 Name Company Title

Subscribed and sworn before me this

I hereby swear or affirm that the information given above is true and correct.

29th. day of **November**, 19**47**Name **Don Phillips**Position **Asst. Dist. Supt.**Representing **Amerada Petroleum Corporation**
Company or OperatorMy commission expires **My Commission Expires May 9 1948**Address **Drawer D, Monument, New Mexico**

Remarks:

APPROVED

Roy Yarbrough
 OIL & GAS INSPECTOR
 Name
 Title