

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

DUPLICATE

MISCELLANEOUS REPORTS ON WELLS

RECEIVED
NOV 26 1947
HOBBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on Plugging Back	X

November 22, 1947

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____

Amerada Petroleum Corporation

J. R. Phillips

Well No. 5 in the _____

Company or Operator

Lease

NE 1/4 NE 1/4

of Sec. 1

T. 20S

R. 36E

N. M. P. M.,

Monument

Field,

Lea

County.

The dates of this work were as follows:

November 19 - 22, 1947

Notice of intention to do the work was ~~(submitted)~~ submitted on Form C-102 on November 18, 1947and approval of the proposed plan was ~~(was not)~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

7532' Drilled Out Depth. Ran Baker Type K Cement Retainer and set at 7589'. Tried for 3 hours to break formation down with water but could not pump into it. Maximum pressures: 5000# tbg., 2500# csg. Dumped 20 sacks of common cement down tubing on top of retainer, pulled up and reversed out 8 sacks of cement. Drilled out cement to 7532' and perforated with Lane Wells from 7190' to 7230', 160 holes. Ran American Packer and 2-7/8" OD, Hydrill Speedtite Tubing w/1-2' perforated sub on bottom of tubing at 7232' and Packer at 7161'. Displaced mud with 185 bbls. of oil and started swabbing. In 22 hrs. to 7:00AM, 11-22-47, recovered 44.73 bbls. of oil. In last 7 hrs. got no fluid out of hole.

Witnessed by D. F. Furse Amerada Petroleum Corporation Foreman
Name Company Title

Subscribed and sworn before me this _____

I hereby swear or affirm that the information given above is true and correct.

22nd. day of November, 1947

Name W. H. TaylorPosition Asst. Dist. Supt.Representing Amerada Petroleum Corporation
Company or Operator

My commission expires _____

Address Drawer D, Monument, New Mexico

Remarks:

APPROVED

Date NOV 26 1947

Roy Garbrough
Name
OIL & GAS INSPECTOR
Title