


OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS



Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on Setting Casing	X

November 4, 1947

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____

Amerada Petroleum Corporation J. R. Phillips Well No. 5 in the
Company or Operator Lease

NE 1 NE 1 of Sec. 1, T. 20S, R. 36E, N. M. P. M.,
Monument Field, Lea County.

The dates of this work were as follows: November 4, 1947

Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on November 2, 1947
and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

9953' Total Depth, Granite. Ran Gamma Ray, Schlumberger, Calipers and Dip Meter. Ran total of 248 joints of 5½" OD, 17#, N-80 & J-55, R-3, 8-RT, Spang SS Casing with 36 joints of N-80 on bottom, 209 joints of J-55 in middle and 3 joints of N-80 on top and set at 9901'. Cemented with 1000 sx. El Toro Cement 3% Howcogel, 500 sx. El Toro Bulk Cement and plug pumped to 3940' at 2:21PM. Lost returns at 2:19PM at 2300'. Final press. 2100#. 41 Larkin Centralizers at: 9896', 9872', 9848', 9824', 9800', 9776', 9752', 9730', 9706', 9680', 9652', 9628', 9606', 9590', 97718', 9690', 9656', 9623', 9589', 9556', 9517', 9485', 9252', 9218', 9184', 9150', 9116', 9082', 9054', 9020', 8973', 8975', 8938', 8901', 8864', 8834', 8594', 8550', 8520', 8500', 8154'. Finished 2:21PM, 11-4-47.

Witnessed by D. F. Furze Amerada Petroleum Corporation Foreman
Name Company Title

Subscribed and sworn before me this _____

I hereby swear or affirm that the information given above is true and correct.

4th. day of November, 1947

Name Dw Phillips

Position Aast. Dist. Supt.

Representing Amerada Petroleum Corporation
Company or Operator

My commission expires _____
My Commission Expires May 9, 1948

Address Drawer D, Monument, New Mexico

Remarks:

APPROVED

Date NOV 12 1947

Roy J. J. J.
OIL & GAS INSPECTOR

Title