

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

RECEIVED
HOBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on Setting 8-5/8" Casing	X

December 19, 1948

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____
Amerada Petroleum Corporation J.R. Phillips Well No. 7 in the _____

Company or Operator Lease
SE 1/4 NE 1/4 of Sec. 1, T. 20S, R. 36E, N. M. P. M.,
Wildcat Field, Lea County.

The dates of this work were as follows: December 18, 1948

Notice of intention to do the work was (~~approved~~) submitted on Form C-102 on December 17, 1948
and approval of the proposed plan was (~~approved~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

5235 Total Depth, Line, Ran 32jts. 8-5/8" OD 36#, N-80, R-3, 8rd. Thd. Spang S.S. Csg. (New) 1288.48' on bottom, 97 jts. 8-5/8" OD 32#, J-55, R-3, 8rd. Thd. Youngstown S.S. Csg. (New) 3895.52' and 2 jt. 8-5/8" OD, 36#, N-80, R-3, 8rd. Thd. Spang S.S. Csg. (New) 477.84'. Csg. set at 5234' Weatherford Scratchers at 5023'-5038'-5053'-5068'-5083'-5098'-5113'-5128'-5143'-5153'-5163'-5173'-5183'-5193'-5203'-5213'-5223'-5227'-5230'-5232' (Total of 20) Baker centralizers set at 5040'-4070'-5100'-5130'-5160'-5190'-5220' (Total of 7) Cemented with 1400Sacks Reg. Bulk cement (1000 ax. mixed 2% Howcogel) 100 sacks Incor, and plug pumped to 5152' with 1400# at 4:00 P.M. 12-18-48

Witnessed by K.V. Stephenson Amerada Petroleum Corporation Foreman
Name Company Title

Subscribed and sworn before me this
19th day of December 1948

Will Hale Taylor
Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name W. G. TaylorPosition Asst. Dist. Supt.

Representing Amerada Petroleum Corporation
Company or Operator

My commission expires _____

Address Drawer D, Monument, New Mexico

Remarks:

Ray Yankrough
Name
Title

APPROVED

Date DEC 21 1948