

COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator Amerada Hess Corporation		8. Farm or Lease Name J. R. Phillips
3. Address of Operator Drawer D, Monument, New Mexico 88265		9. Well No. 9
4. Location of Well UNIT LETTER <u>A</u> <u>660</u> FEET FROM THE <u>North</u> LINE AND <u>360</u> FEET FROM THE <u>East</u> LINE, SECTION <u>1</u> TOWNSHIP <u>20-S</u> RANGE <u>36-E</u> NMPM.		10. Field and Pool, or Wildcat Eunice-Monument G/SA
15. Elevation (Show whether DF, RT, GR, etc.) 3588' DF		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input checked="" type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Pulled rods, pump & tbg. Ran water entry survey and determined that water was being produced from bottom section of 7" csg. perf. Ran gauge ring to 3700'. Set cement retainer on wire line at 3689'. Squeezed lower part of Grayburg San Andres zone thru 7" csg. perf. fr. 3694' to 3704' with 75 sks. cement. Re-ran 2-7/8" tbg., pump and rods and resumed production from Grayburg San Andres zone thru 7" csg. perf. fr. 3674' to 3684'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>E. B. Fisher</u>	TITLE <u>Supv. Adm. Ser.</u>	DATE <u>3-23-77</u>
APPROVED BY <u>Jerry Sexton</u>	TITLE <u>Dist 1, Supv.</u>	DATE <u>3-23-77</u>
CONDITIONS OF APPROVAL, IF ANY:		