## NEW EXICO OIL CONSERVATION CO. ISSION

Santa Fe, New Mexico

### **MISCELLANEOUS NOTICES**

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or its agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of		
NOTICE OF INTENTION TO TEST CASING SHUT-OFF	X NOTICE OF INTEN	TION TO SHOOT OR REAT WELL
NOTICE OF INTENTION TO CHANGE PLANS	NOTICE OF INTENT OTHERWISE AL	TION TO PULL OR TER CASING
NOTICE OF INTENTION TO REPAIR WELL		TION TO PLUG WELL
NOTICE OF INTENTION TO DEEPEN WELL		
Morament, New	Mexico	June 25, 1956
OIL CONSERVATION COMMISSION,	Place	Date
anta Fe, New Mexico.		
entlemen:		
ollowing is a notice of intentiton to do certain work a	s described below at the	
mamada 70-4 5 a	State "D" Well N	
Company or Operator Lease		
, 10	, N. M. P. M., <b>No</b>	mment Fie
County.		
6-5/8" <b>20# 10</b> -thd. New Electric w	elded casing was set	
6-5/8" 30# 10-thd. New Electric we mented by the Halliburton Method with Casing and fittings will be testedudistrubed for thirty minutes. If no dilled out of easingand the same test disturbed for thirty minutes. If no disturbed for thirty minutes.	olded casing was set 170 sacks of cement. with 1200# pump press lrop in pressure ress	in this well at 3790.  Ture and allowed to start the coment will be
6-5/8" 20f 10-time. New Electric we emented by the Halliburton Method with Casing and fittings will be testedudistructed for thirty minutes. If no decilled out of easingand the same test disturbed for thirty minutes. If no desire the same test disturbed for thirty minutes.	olded casing was set 170 sacks of cement. With 1200# pump press trop in pressure resu of 1200# again applicate in pressure resu	in this well at 3790.  Ture and allowed to star  Its the coment will be
6-5/8" 20f 10-thd. New Electric we smented by the Halliburton Method with Casing and fittings will be testedudistrubed for thirty minutes. If no drilled out of easing and the same test adisturbed for thirty minutes. If no dresumed.	olded casing was set 170 sacks of cement. With 1200# pump press trop in pressure resu of 1200# again applicate in pressure resu	in this well at 3790° .  The sure and allowed to stand the cement will be sed and allowed to stand the drilling will to the drilling will
6-5/8" 20f 10-thd. New Electric we mented by the Halliburton Method with Casing and fittings will be tested distribed for thirty minutes. If no decilled out of ensingment the same test disturbed for thirty minutes. If no decreased.	elded casing was set 170 sacks of cement. with 1200# pump pressure resurce for 1200# again applicate in pressure resure in pressure resure in pressure resure.	in this well at 3790.  Sure and allowed to start the cement will be ed and allowed to stand its the drilling will the dr
6-5/8" 20f 10-thd. New Electric we smented by the Halliburton Method with Casing and fittings will be tested adistrubed for thirty minutes. If no decilled out of easing and the same test adisturbed for thirty minutes. If no decrease the same test adisturbed for thirty minutes. If no decrease the same test adisturbed for thirty minutes. If no decrease the same test adisturbed for thirty minutes.	elded casing was set 170 sacks of cement. with 1200# pump pressure resurce for 1200# again applicate in pressure resure in pressure resure in pressure resure.	in this well at 3790° and allowed to start the cement will be ed and allowed to stand lts the drilling will in
6-5/8" 20f 10-thd. New Electric we emented by the Halliburton Method with Casing and fittings will be testedudistrubed for thirty minutes. If no drilled out of easing and the same test edisturbed for thirty minutes. If no de resumed.	alded casing was set 170 sacks of cement.  with 1200# pump press result of 1200# again application in pressure resulting in pressure	in this well at 3790° in this well at 3790° in this well at 3790° in the send allowed to start the cement will be sed and allowed to stand lts the drilling will the drilling will the drilling will the company or Operator
6-5/8" 30f 10-thd. New Electric we emented by the Halliburton Method with Casing and fittings will be testedy adistrubed for thirty minutes. If no drilled out of easing and the same test adisturbed for thirty minutes. If no de resumed.	alded casing was set 170 sacks of cement.  With 1200# pump press result of 1200# again appliately in pressure resulting in pressure	in this well at 3790° in this well at 3790° in this well at 3790° in the standard st
6-5/8" 20f 10-thd. New Electric we emented by the Halliburton Method with Casing and fittings will be testedudistrubed for thirty minutes. If no drilled out of easing and the same test edisturbed for thirty minutes. If no de resumed.	alded casing was set 170 sacks of cement.  With 1200# pump press result of 1200# again appliately in pressure resulting in pressure	in this well at 3790.  Gure and allowed to stand its the coment will be sed and allowed to stand its the drilling will be drilling will its the drilling will its the drilling will be drilling will be drilling will be dri

# 

TO DESCRIPTION OF THE PROPERTY OF THE PROPERTY

en de la companya de la co

 $(x,y) = \mathbf{G}_{\mathbf{x}}^{T}(x,y) + (x,y) + (x,y) + (x,y)$ 

and the second of the second