


OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS



Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	<input checked="" type="checkbox"/>
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

December 20, 1949

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____
Amerada Petroleum Corporation State D Well No. 4 in the _____
Company or Operator Lease

NE 1/4 of the NW 1/4 of Sec. 1, T. 20, R. 36, N. M. P. M.,
Monument Field, Lee County.

The dates of this work were as follows: December 10, 1949

Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on December 10, 1949
and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

3900' - Total Depth, 3877' Plug Back Depth, 5 1/2" Casing set at 3820'
Rigged up Mobil Unit and pulled 2-7/8" Tubing. Ran Sand Pump and cleaned out hole to T.D.
Ran Lane-Wells Gamma Ray and Neutron Survey. Lane-Wells checked bottom at 2898'
Dumped at intervals a total of 17 sacks of Incon Cement mixed with Wellite. Measured up
and found top of plug at 3877'. Ran back in hole w/ 2-7/8" Tubing and Packer. Set Packer
at 3734' and Tubing at 3871' with 6 Olsco Flow Valves set at 1202', 2000', 2512', 2960',
3345' & 3698'. Kicked Well off with Input gas and in 24 hours well flowed 243.66 bbls. of
oil and 81.34 bbls. of water. GFR 1078, GOR 144. No Input gas used after well kicked-off
Well placed back on production.

Witnessed by D.F. Furse Amerada Pet. Corp. Foreman
Name Company Title

Subscribed and sworn before me this _____
4 day of Jan. 1950

I hereby swear or affirm that the information given above
is true and correct.

Name Don J. [Signature]
Position Assistant District Superintendent
Representing Amerada Petroleum Corporation
Company or Operator

Notary Public

My commission expires 10/24/53

Address Drawer "D" Monument, New Mexico

Remarks:

APPROVED

JAN 4 1950

Ray [Signature]
Name
Title