Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

EPORT ON BEGINNING DRILLING OPERATIONS	RI	EPORT ON RI	SPAIRING WELL	
EPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL	RI	EPORT ON PU	LLING OR OTH	ERWISE
SPORT ON RESULT OF TEST OF CASING SHUT-OFF	X RI	EPORT ON DE	EPENING WELL	
EPORT ON RESULT OF PLUGGING OF WELL				
Monument, 1	New Mexico	In .	M.	ay 27, 1937
L CONSERVATION COMMISSION,		ia e		Date
inta Fe, New Mexico.		u		
entlemen:				
ollowing is a report on the work done and the res	ults obtained u	nder the head	ling noted above	at the
erada Petroleum Corporation		Sta	te "D"Well No	in the
Company or Operator		Lease 20	. 56	
or sec.	, T			, N. M. P. M.,
mument Field,		.68	······································	County.
DETAILED ACCOUNT OF W 1/2" 17# 10-Thd. New Seamless casing and fittings were tested with 1	ORK DONE	E AND RE	SULTS OBTA	and cemented by
DETAILED ACCOUNT OF W 1/8" 17# 10-Thd. New Seamless casing and fittings were tested with 1 disturbed for thirty minutes. No disturbed out of the casing and the same dallowed to stand undisturbed for the drilling was then resumed.	ORK DONE ng was set 1200# pump rop in pres test of 1 thirty minu	in this work pressure results. No	ell at 3820 and allowed lted so the pressure # drop inppres	to stand cement was then as again applied ssure resulted so
DETAILED ACCOUNT OF W 1/2" 17# 10-Thd. New Seemless casing and fittings were tested with 1 disturbed for thirty minutes. No dilled out of the casing and the same dallowed to stand undisturbed for	ork Done ng was set 1200# pump rop in prese test of 1 thirty minu Rowan Dri	in this w pressure ssure resu 200# pump	ell at 3820 and allowed lted so the pressure # drop inppres	and cemented by to stand cement was then as again applied

Title

\$ 100 miles

en de la composition La composition de la

en de la composition La composition de la

to the second of the second of

en de la composition La composition de la

•

en de la composition La composition de la