Form C-103

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on Plugging Back	X

April 22, 1948 (Date) Monument, New Mexico (Place)

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the Amerada Petroleum Corporation (Company or Operator) State D (Lease) Well No. 5 in the NE¼ NW¼ of Sec. 1, T. 20S, R. 36E, N. M. P. M., Monument-Paddock Field, Lea County.

The dates of this work were as follows: April 21,22, 1948

Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on April 21, 1948 and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

5220' Total & Drilled Out Depth. Set Baker Model K Cement Retainer rigged up as Bridging Plug at 5212'. Spotted 5 sx Incor Cement on top of plug back up to 5170'. Flushed with 19½ bbls. water, pulled up to 5162' and reversed out about ½ bbl. muddy water at 10:20PM, 4-21-48. Found top of cement at 5175' and washed out to 5208' at 4:25AM, 4-22-48, Perforated 5½" Casing with Lane Wells 5150' - 5165', 60 holes. Ran 166 jts. of 2-3/8"OD, EUE, 4.7#, J-55, R-2, 8-RT, SS Tubing and Guiberson Packer w/1-3' perf. sub on bottom bull plugged and 1-4' handling sub. Displaced water with 120 bbls. of oil and set packer at 5091', bottom of tubing at 5192'.

Witnessed by C. E. Telge (Name) Amerada Petroleum Corporation (Company) Farm Boss (Title)

Subscribed and sworn before me this 22nd day of April 19 48

Will Hale Taylor
Notary Public

My commission expires

I hereby swear or affirm that the information given above is true and correct.

Name

Position Asst. Dist. Supt.

Representing Amerada Petroleum Corporation
Company or Operator

Address Drawer D, Monument, New Mexico

Remarks: APPROVED SEP 2 1948

Name

Title