

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

JUL 29 3 24 PM '69

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease  
State ☒ Fee ☐

5. State Oil & Gas Lease No.  
**B-1386**

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator <b>Amerada Hess Corporation</b>	8. Farm or Lease Name <b>State "H"</b>
3. Address of Operator <b>P. O. Box 1920 - Hobbs, New Mexico</b>	9. Well No. <b>1</b>
4. Location of Well UNIT LETTER <b>0</b> <b>660</b> FEET FROM THE <b>South</b> LINE AND <b>1980</b> FEET FROM THE <b>East</b> LINE, SECTION <b>1</b> TOWNSHIP <b>20-S</b> RANGE <b>36-E</b> NMPM.	10. Field and Pool, or Wildcat <b>Grayburg San Andres</b>
15. Elevation (Show whether DF, RT, GR, etc.) <b>3571' DF</b>	12. County <b>Lea</b>

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input checked="" type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

**Pull rods, pump and tubing. Run tubing and packer and squeeze perforations 3730' to 3745'. Drill out to 3790'. Perforate open hole 3785' to 3790' and 7" casing from 3760' to 3785' and swab test. If necessary, acidize with diverter. Resume production.**

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u><i>W. M. St. John</i></u>	TITLE <b>District Clerk</b>	DATE <b>July 28, 1969</b>
APPROVED BY <u><i>John W. Runyan</i></u>	TITLE <b>Geologist</b>	DATE <b>JUL 29 1969</b>
CONDITIONS OF APPROVAL, IF ANY:		