

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

RECEIVED
DEC 1 1949

NOBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

| | | | |
|--|--|--|---|
| REPORT ON BEGINNING DRILLING OPERATIONS | | REPORT ON REPAIRING WELL | |
| REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL | | REPORT ON PULLING OR OTHERWISE ALTERING CASING | X |
| REPORT ON RESULT OF TEST OF CASING SHUT-OFF | | REPORT ON DEEPENING WELL | |
| REPORT ON RESULT OF PLUGGING OF WELL | | | |

December 1, 1949

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____
Amerada Petroleum Corporation State H Well No. 1 in the _____

Company or Operator
SW 1/4 of the SE 1/4 of Sec. 1, T. 20S, R. 36E, N. M. P. M.,
Monument Field, Lea County.

The dates of this work were as follows: November 15, 1949

Notice of intention to do the work was (amended) submitted on Form C-102 on November 15, 1949 and approval of the proposed plan was (amended) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

3877' Total Depth, 3866' Plug Back Depth. Cleaned hole out to Total Depth and ran Lane Wells Gamma Ray & Neutron Surveys. Dumped a total of 190 gallons of Dowell Plastic but could only get 1' of 11' required fill. Dumped four sacks comm. cement mixed w/ wellite, measured up had 1' fill. Dumped additional 2 sacks of cement, measured up and had total of 7' fill. Dumped 1 sack of Incor cement mixed w/ wellite, measured up and found top of plug at 3866' (total 11' fill) Ran back with tubing & packer with five (5) Olasco Flow Valves set at 1361', 2283', 2954', 3464' & 3920'. Kicked well off with input gas and in 17 hours well flowed 92.50 bbls of oil & 5.90 bbls. of water. GOR 2640. No input gas used after well kicked off. Work-over complete

Witnessed by E.E. Shirley Amerada Petroleum Corporation Head Gauger
Name Company Title

Subscribed and sworn before me this

13 day of Dec. 1949

I hereby swear or affirm that the information given above is true and correct.

Name Don Topp
Position Assistant District Superintendent

Representing Amerada Petroleum Corporation
Company or Operator

My commission expires 10/24/53

Address Drawer "D", Monument, New Mexico

Remarks:

APPROVED

DEC 4 1949

Date.....

Ray J. Yarbrough
Title