NEW MEXICO OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

	Indicate nature of	nonce by cneck	ing below:			
OTICE OF INTENTION TO THE SHUT-OFF	EST CASING	X NOTICE CHEM	OF INTENT	TION TO SHO REAT WELL	OT OR	
OTICE OF INTENTION TO CH	IANGE PLANS	NOTICE OTHE	OF INTENTER	TION TO PULI	LOR	
OTICE OF INTENTION TO RI	EPAIR WELL			TION TO PLU	G WELL	
OTICE OF INTENTION TO DI	EEPEN WELL					
	Monum	ent, New Mex	deo	November	27, 1951	
		P	lace		Date	••••••••••
lowing is a notice of intention crade petroleum Corpo	to do certain work as State	described below	at the	Well No	3 _{in} NE	-NW-S
Company or Operator Sec, T, T	, R. 36-B	, N. M. P. M.,	Honumen	t-Blinebry		Field
8	County	,				
	•	BUBUSED DI	ANOEV	IODIZ		
FUI FOLLOW INSTRU 307' - Total Depth - 1 Ran 55 Jts of 16 set at 2302' am regular and 50 11/26/51. Hax	LI DETAILS OF P. CTIONS IN THE RULL Lime. Finished of -3/4" OD 40.5# i cemented with 1 sax Incor cement Pump pressure 100	es and regui irilling 13- 1-55 R-3 8-F 1000 sacks r - Total 150 00#. Cement	-3/4" hol T SS Cag regular m O sax.	THE COMM e @ 7:35 A . New for : exied 3% J Plug to 22	M, 11/26/ 2299 Ca el, 450 a	sing acks
FUI FOLLOW INSTRU 2307' - Total Depth - 1 Ran 55 Jts of 16 set at 2302' and regular and 50 11/26/51. Max	LI DETAILS OF P. CTIONS IN THE RULI Lime. Finished of 0-3/4" OD 40.5# I cemented with 1	es and regui irilling 13- 1-55 R-3 8-F 1000 sacks r - Total 150 00#. Cement	-3/4" hol T SS Cag regular m O sax.	THE COMM e @ 7:35 A . New for : exied 3% J Plug to 22	M, 11/26/ 2299 Ca el, 450 a	sing acks
FUI FOLLOW INSTRU 307' - Total Depth - 1 Ran 55 Jts of 16 set at 2302' am regular and 50 11/26/51. Hax approximately 2	LI DETAILS OF P. CTIONS IN THE RULL Lime. Finished of -3/4" OD 40.5# i cemented with 1 sax Incor cement Pump pressure 100	es and Regui irilling 13- I-55 R-3 8-R 1000 sacks r - Total 150 00#. Cement t Casing Shu	LATIONS OF A STATE OF SAX. L. Circula of the Circu	THE COMM e @ 7:35 A . New for : exied 3% J Plug to 22 ted. After	M, 11/26/92299 Ca 2299 Ca 21, 450 s 15' at 7: 2r W.O.C.	sing acks
FUI FOLLOW INSTRU 2307' - Total Depth - 1 Ran 55 Jts of 16 set at 2302' am regular and 50 11/26/51. Max approximately 2	LL DETAILS OF P. CTIONS IN THE RULL Lime. Finished of -3/4" OD 40.5# i cemented with 1 sax Incor cement Pump pressure 100 4 hours will test	es and Regui irilling 13- I-55 R-3 8-R 1000 sacks r - Total 150 00#. Cement t Casing Shu	LATIONS OF A STATE OF SAX. L. Circula of the Circu	F THE COMM e @ 7:35 A . New for a exied 3% J Plug to 22 ted. Afte	M, 11/26/92299 Ca 2299 Ca 21, 450 s 15' at 7: 2r W.O.C.	sing acks
FUI FOLLOW INSTRU 2307' - Total Depth - 1 Ran 55 Jts of 16 set at 2302' am regular and 50 11/26/51. Max approximately 2	LL DETAILS OF P. CTIONS IN THE RULL Lime. Finished of -3/4" OD 40.5# i cemented with 1 sax Incor cement Pump pressure 100 4 hours will test	irilling 13- I-55 R-3 8-B 1000 sacks r - Total 150 00#. Cement t Casing Shu	Assista	THE COMM e @ 7:35 A . New for a exied 3% J Plug to 22 ted. After Company or o	M, 11/26/2299'. Ca el, 450 a 15' at 7: or W.O.C.	acks 15 PM for
FUI FOLLOW INSTRU 2307' - Total Depth - 1 Ran 55 Jts of 16 set at 2302' am regular and 50 11/26/51. Max approximately 2 proved	LL DETAILS OF P. CTIONS IN THE RULL Lime. Finished of -3/4" OD 40.5# i cemented with 1 sax Incor cement Pump pressure 100 4 hours will test	irilling 13- I-55 R-3 8-F 1000 sacks r - Total 150 00%. Cement t Casing Shu	Assista Send con	THE COMM e @ 7:35 A . New for a exied 3% J Plug to 22 ted. After Company or	M, 11/26/2299'. Ca al, 450 a 15' at 7: ar W.O.C.	acks 15 PM for tender