

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Bonito Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-04155
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. A 1375
7. Lease Name or Unit Agreement Name STATE "I"
8. Well No. 1
9. Pool name or Wildcat EUNICE MONUMENT G/SA

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	
2. Name of Operator AMERADA HESS CORPORATION	
3. Address of Operator DRAWER D, MONUMENT, NEW MEXICO 88265	
4. Well Location Unit Letter C : 660 Feet From The NORTH Line and 1980 Feet From The WEST Line Section 2 Township 20S Range 36E NMPM LEA County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3606' DF	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☒ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

MOVED IN AND RIGGED UP PULLING UNIT, TIH W/BIT AND TUBING & TAGGED FILL AT 3882'. RAN HYDROSTATIC BAILER AND CLEANED OUT FILL FROM 3882' TO 3905'. RAN 4-1/2" PACKER AND SWABBED WELL. RECOVERED 2 BBLS. WATER. ACIDIZED G/SA PERFS. FR. 3892' TO 3919' W/1000 GALS. NEFE ACID. SWABBED WELL FOR 2 DAYS FOR A TOTAL OF 7 BBLS. RAN TANDEM BOMBS SET AT 3850' FOR 72 HOURS. WELL STABILIZED. PULLED TBG. AND PACKER, SET CIBP AT 3875'. TESTED CIBP TO 2500#, SPOTTED 50 GALS. ACID AND PERFORATED G/SA FROM 3822' TO 3851' W/2 SPF FOR A TOTAL OF 30 SHOTS USING 3-3/8" CASING GUN. ACIDIZED PERFS. WITH 750 GALS. 15% NEFE ACID. MAX. PRESS. 900#. ISIP VAC., SWABBED WELL AND RECOVERED 1-1/2 BBLS. SWABBED DRY. REMOVED BOP AND CI FOR EVALUATION.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Cindy Robertson TITLE Sr. Admin. Staff Assistant DATE 7/19/91
TYPE OR PRINT NAME TELEPHONE NO.

(This space for State Use)

APPROVED BY _____ TITLE _____ DATE JUL 22 1991
CONDITIONS OF APPROVAL, IF ANY: