

## OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	<input checked="" type="checkbox"/>
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

September 6, 1949

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_

Amerada Petroleum Corporation State J Well No. 3 in the \_\_\_\_\_

SE<sub>1</sub> of the SW<sub>4</sub> Company or Operator \_\_\_\_\_ Lease \_\_\_\_\_  
 of Sec. 2, T. 20, R. 36, N. M. P. M.,  
Monument Field, Lea County.

The dates of this work were as follows: August 30, 1949

Notice of intention to do the work was ~~not~~ submitted on Form C-102 on August 30 19 49  
 and approval of the proposed plan was ~~not~~ obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

3930' Total Depth. 6-5/8" OD Casing set at 3810'

Rigged up Rotary Tools and went in hole with Baash-Ross Cutting Tool and cut  
 6-5/8" OD Casing off at 2430'. Pulled out and layed down 85 Joints of 6-5/8" OD Casing.  
 Ran back in hole with 84 Joints of 6-5/8" OD Casing in good condition and one  
 7-5/8" OD x 6-5/8" ID x 4' Long Baash-Ross Casing Bowl, to make splice.

Tested 6-5/8" OD Casing with 1400# for 1/2 hour, no pressure drop. Ran back in hole  
 with tubing and packer and swabbed well in. In 15 hours well flowed 246.25 bbls. oil  
 and 40.00 bbls. of water. GOR 1554 - Work-over complete.

Witnessed by E.E. Shirley Amerada Petroleum Corporation Head Gauger  
 Name Company Title

Subscribed and sworn before me this \_\_\_\_\_

13 day of Dec. 19 49

Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name Don 10/22Position Assistant District SuperintendentRepresenting Amerada Petroleum Corporation  
Company or OperatorMy commission expires 10/24/53Address Drawer "D" Monument, New Mexico

Remarks:

APPROVED

DEC 14 1949

Roy Yarbrough

Title