

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	<input checked="" type="checkbox"/>
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

September 4, 1948

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____
Amerada Petroleum Corporation State S Well No. 2 in the _____

Company or Operator SW $\frac{1}{4}$ SW $\frac{1}{4}$ of Sec. 2, T. 20S, R. 36E, N. M. P. M.,
Monument Field, Lea County.

The dates of this work were as follows: August 30 - September 4, 1948

Notice of intention to do the work was (~~submitted~~) submitted on Form C-102 on August 27, 1948
and approval of the proposed plan was (~~obtained~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

3920' Total Depth, Lime. Tried to kill well but gas was blowing at rate of 8,000,000 cu. ft. per day. Used Halliburton and killed well with 120 bbls. water, 1100# pressure. Pulled 2-7/8" OD, EUE, tbg. and set Baker Bridging Plug in 6-5/8" OD csg. at 3730' with 5 sx cement. Ran Retrievable Retainer and found leak in 6-5/8" OD csg. at 1114'-16'. Cut off csg. at 2350' and pulled 81 jts. and piece of 6-5/8" OD, 20#, casing. Ran Beach-Ross Casing Bowl and 72 jts. 6-5/8" OD, 20#, 24# and 26# casing and spliced casing at 2350'. Ran 5-5/8" bit, drilled out plug and cleaned out hole to bottom. Ran Dowell Spinner Survey and hole took fluid at 3754'-66', 80%; 3778'-88', 15%; 3794'-96', 5%. Plugged back with 19 gals. Dowell Plastic 3920' to 3907'. Set packer at 3713', tbg. @ 3902' and started swabbing 4:00AM, 9-4-48.

Witnessed by C. E. Telge Name Amerada Pet. Corp. Company Farm Boss Title

Subscribed and sworn before me this _____

I hereby swear or affirm that the information given above is true and correct.

4th. day of September 1948

Name Will Hails Taylor

Position Asst. Dist. Supt.

Notary Public

Representing Amerada Petroleum Corporation

Company or Operator

My commission expires _____

Address Drawer D, Monument, New Mexico

Remarks:

APPROVED

Date SEP 2 1948

Will Hails Taylor
Name
Title