


DUPLICATE

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS



Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	X
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

Monument, New Mexico

Place

July 3, 1946

Date

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Amarada Petroleum Corporation C. H. Weir Well No. 2 in the
Company or Operator Lease

NW $\frac{1}{4}$ of NW $\frac{1}{4}$ of Sec. 2, T. 20 S, R. 36 E, N. M. P. M.,
Monument Field, Lea County.

The dates of this work were as follows: June 5, to June 24, 1946

Notice of intention to do the work ~~was~~ (was not) submitted on Form C-102 on 19

and approval of the proposed plan ~~was~~ (was not) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

3930' Total Depth, Drilled out retainer and cement to 2500' and tested with Halliburton pump and could pump into casing, Dumped 400 Sax Common Cement and pumped Halliburton Plug to 2064' and put up 2000# and held it for 20 minutes on June 6th, 1946, On June 8, went in hole and found top of cement at 1997' and drilled cement to 2268' and ran out of cement at 2400', put up 1300# Pressure for 30 mins at 2264' and was OK. Drilled out to 3930' and swabbed well and did not have enough gas to flow well and on June 24, Acidized with 500 Gals Dowell Acid XF-18-W-9 and collapsed packer at 3844' and swabbed well for 2 hours and started flowing. Made 177.15 Bbls Oil 160.39 Bbls Water for 24 hrs

Witnessed by J. H. Choate, Don Topper, Amarada Pet. Corp., Asst. Dist. Supt.
Name Company Title

Subscribed and sworn before me this

I hereby swear or affirm that the information given above is true and correct.

3 day of July, 1946

Name Don Topper

Will Haile Taylor
Notary Public

Position Asst. Dist. Supt.

Representing Amarada Pet. Corp.,
Company or Operator

My commission expires

Address Drawer D, Monument, New Mexico.

Remarks:

APPROVED

Date JUL 8 1946

Ray Yankrough
Oil & Gas Inspector
Name Title