


## OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS



DUPLICATE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	X
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

Monument, New Mexico

Place

July 3, 1946

Date

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_

Amerada Petroleum Corporation

C. H. Weir

Well No. 2

in the

Company or Operator

Lease

NW 1/4 of NW 1/4

of Sec. 2

T. 20S

R. 36E

N. M. P. M.,

Monument

Field,

Lea

County.

The dates of this work were as follows: May 20th to May 25th, 1946

Notice of intention to do the work ~~was~~ (was not) submitted on Form C-102 on \_\_\_\_\_ 19 \_\_\_\_\_and approval of the proposed plan ~~was~~ (was not) obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

3920' Total Depth, Tried to set Bolshevik Cave Catcher for Umbrella Bridge at 3829' no Results, filled hole to 3816' with pea gravel and dumped 8 Gallons of Dowell Plastic and filled up to 3810', Ran Dowell Pilot Survey and found leak in 6 5/8" Casing at 2264', Set Model K Baker Cement Retainer at 3500' and dumped 4 sacks Incon Cement on top of it with Cement Dump Bailer, and Set another Model K Cement Retainer at 2007' and cemented between 6 5/8" & 8 5/8" Casing with 500 Sax Common Cement and pressure built up to 850# on last 100 Sacks, on May 24, 1946. On May 25, 1946 ran steel line and found top of cement at 1188' inside of 6 5/8" Casing, ran temperature survey and found top of cement at 350' between 6 5/8" and 8 5/8" Casing

Witnessed by Don Topper, Name Amerada Pet. Corp., Asst. Dist. Supt.

Subscribed and sworn before me this \_\_\_\_\_

I hereby swear or affirm that the information given above is true and correct.

3 day of July, 1946

Name Don Topper

Position Asst. Dist. Supt.

Representing Amerada Pet. Corp.,  
Company or Operator

My commission expires \_\_\_\_\_

Address Drawer D, Monument, New Mexico.

Remarks:

APPROVED

Date JUL 8 1946

Roy Yurbrough  
Name  
Oil & Gas Inspector  
Title