

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

DUPLICATE

RECEIVED
JUL 8 1946
OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within the office specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	X
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

Monument, New Mexico,

Place

July 3, 1946

Date

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum Corporation C. H. Weir Well No. 2 in the
Company or Operator Lease

NW 1/4 of NW 1/4 of Sec. 2, T. 20S, R. 32E, N. M. P. M.,
Monument, Lea Field, Lea County.

The dates of this work were as follows: May 26th to June 4, 1946

Notice of intention to do the work ~~was~~ (was not) submitted on Form C-102 on _____ 19____
and approval of the proposed plan ~~was~~ (was not) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

3930' Total Depth, Drilled cement from 1188' to 1208' and went out of cement and found top of Retainer at 2007' and tested with 800# for 30 Mins and was OK, drilled Retainer and tested with 800# for 30 mins and was OK, drilled found top of cement under retainer at 2067' and went out of cement at 2276', ran Tubing in hole to 3500' and put 1000# Pressure on Casing with Dowell and found pump into Casing. Ran Halliburton Plug and found leak in casing at 2264' and set another Baker Model K Cement Retainer at 1975' and pumped in 300 Sack Cement and built up 1200# Pressure, and pumped 350 Sacks Incor and 650 Sacks Commons Cement in 5 stages.

Witnessed by Don Tepper, Amerada Pet. Corp. Asst. Dist. Supt.
Name Company Title

Subscribed and sworn before me this _____

I hereby swear or affirm that the information given above is true and correct.

3 day of July, 19 46

Name Don Tepper

Position Asst. Dist. Supt.

Will Haile Taylor
Notary Public

Representing Amerada Pet. Corp.,
Company or Operator

My commission expires _____

Address Drawer D, Monument, New Mexi co.

Remarks:

APPROVED

Date JUL 8 1946

Ray Yushrough
Name
Oil & Gas Inspector
Title