Submit 3 Copies to Appropriate District Office

State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

P.O. Box 1980, Hobbs NM 88241-1980 DISTRICT II P.O. Drawer DD, Artesia, NM 88210	OIL CONSERVATION DIVISION 2040 Pacheco St. Santa Fe, NM 87505		WELL API NO. 30-025-04165 5. Indicate Type of Lease
DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410			STATE X F 6. State Oil & Gas Lease No.
	NO DEDODTS ON WE		A-1375-39
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			7. Lease Name or Unit Agreement Name North Monument G/SA Unit Blk.
1. Type of Well: OIL GAS WELL OTHER Water Injection Well			
2. Name of Operator			8. Well No.
Amerada Hess Corporation 3. Address of Operator P. 0. Box 840, Seminole, Texas 79360			9. Pool name or Wildcat Eunice Monument G/SA
4. Well Location	t From The North	Line and66	
Section 2 Tow	vnship 20S p	Range 36E	
	111311112	her DF, RKB, RT, GR, etc 3590' GL	
11. Check Appropri			Report, or Other Data
NOTICE OF INTER	TION TO:	508	SEQUENT REPORT OF:
PERFORM REMEDIAL WORK U	UG AND ABANDON	REMEDIAL WORK	X ALTERING CASING
TEMPORARILY ABANDON	HANGE PLANS	COMMENCE DRILLING	OPNS. PLUG AND ABANDONN
PULL OR ALTER CASING		CASING TEST AND CE	
		CASING TEST AND CE	MEN I JOB 🗀
OTHER:		OTHER:	
12. Describe Proposed or Completed Operations (work) SEE RULE 1103.	(Clearly state all pertinent de	tails, and give pertinent dat	tes, including estimated date of starting any
5-3 thru 5-12-2000			
MIRU Tyler Well Svc. pulling ustagged top of fill at 3935' & 6 Dumped 3' cement on top of same Halliburton Svc. pumped 84 sks & tagged top of cement at 3608 squeeze to 500 PSI. Drld. ceme 3936'. TIH w/7" J-Lok inj. pkfluid & press. tested csg. & plinstalled wellhead. RDPU, clean	dumped 135 sks. sand d. Top of cement at . Class C. cement w/ '. Drld. cement, re ent to 3762' & washe r. on 2-3/8' poly-li kr. to 460 PSI for 3	d in O.H. Tagged to 3759'. TIH w/ceme 'LAP-1 Latex addition etainer, & cement to ed to 3820'. Circ. ined tbg. & set pkr 30 min. Chart atta	op of sand at 3762'. ent retainer set at 3610'. ve. WOC. TIH w/6-1/8" bit o 3750'. Press. tested sand out fr. 3820'. at 3657'. Circ. pkr.
I hereby certify that the information above is true and com-		ge and belief.	II DATE 5-24-20
TYPE OR PRINT NAME ROY L. Wheeler, Jr.			TELEPHONE NO. 915 758
TYPE OR PRINT NAME ROY L. Wheeler, Jr. (This space for State Use)	M. Salah III da	7/4	TELEPHONE NO. 915 758

