## NE MEXICO OIL CONSERVATION COMISSION

Santa Fe, New Mexico

## **MISCELLANEOUS NOTICES**

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or its agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

### Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF	X	NOTICE OF INTEN CHEMICALLY TH		ĸ
		NOPLOP OF INTENT		
NOTICE OF INTENTION TO CHANGE PLANS	X	NOTICE OF INTENT OTHERWISE ALT		
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENT	ION TO PLUG WELL	2
NOTICE OF INTENTION TO DEEPEN WELL				
	Hobbs,	New Mexico	5-20-3	56
	· · · · ·	Place	Dat	e
OIL CONSERVATION COMMISSION,				
Santa Fe, New Mexico.				
Gentlemen:				
•			his That Com	
Following is a notice of intentiton to do certain w		ribed below at the	TO THET DU	opry vo
Anderson-Prichard Prod. Corp.	1	StateWell N	<b>1</b>	C SW ND
Company or Operator Lease	413			
of Sec. 21 2, T. 208, R. 3	<b>75</b> , N.	М. Р. М., Мо	nument	Field.
Lea				1014)
County.				

# FULL DETAILS OF PROPOSED PLAN OF WORK

Follow instructions in the rules and regulations of the commission 13" OD - 40# - 8 thd. New Lap Weld Casing cemented at 265' with 250 sacks common cement May 8, 1936. Total Depth of Hole 270'. To drill plug and bail hole dry for water shut-off test on May 11, 1936

Permission is request/to complete well to use braden head gas from between 9-5/8" casing and 7" casing. Casing and cementing program as follows: Set not less than 250' 13" OD - 40# New Lapweld casing and cement back to surface; set not less than 2500' 9-5/8" - 40# New API Grade C Seamless casing and cement with 600 sks. common cement; set 7" - 24# New API Grade C Seamless Casing on top of pay and cement with 50 sks. common cement. 13" casing cement job shall set not less than forty eight hours before testing; other strings shall set not less than seventy two hours before testing

DUPLICATE

MAY 2 6 1936 Approved	Ohio Fuel Supply Company - Anderson-Prichard Production Corp.		
OIL CONSERVATION COMMISSION, By Utility and Deprotor	By <u>Sup rintendent</u>		
	Send communications regarding well to		
	Name Frank Gray		
	Address Box 301		
	Hobbs, New Mexico		

. . . . . . . .

1 ANT ROLLING AND SOL

## THE REPORT OF THE PARTY OF THE

Set as no bodeas a collector de la compositiona de la collector de la collector de la collector de la collector Per el collector de la colladad de la collector Ade collector de la collector foit de la collector estator de la collector de foit de la collector foit de la collector de foit de la collector de collector de la collector de .

and the second second second second second second second second

and a second s 

÷ : .

(1996) a classification 249(30) (26) (31) (36) (35)

No. No. No. No. No. No. 2010 Michael Michael and Michael and Annual Con-

. . . . . . . Ę

2 19 10 10 10 **1** M R R R R R R R R

1997 (c. 1993)

14. 1. 1. 1. 1. and the second second 

. . 

5 3 . -

an an an Araba ( Carlon Car Carlon C . ' .

n ann an Stairte Stairte Stairte Stairte ند ب<sup>2</sup> د. ا -. , • <sup>#</sup>

. . **.** . 19<sup>2</sup> . • • ÷ •

#### \*\*\*. i

*.* • ; • and the second second

and the state of the

i a si i