



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Las Cruces
Lease No. LC 091622 (b)
Unit N.M.P.U.

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Sanborn 1-9 No. 1

Hobbs, New Mexico November 24, 1954

Well No. 1 is located 660 ft. from [N] line and 660 ft. from [E] line of sec. 9

1/4 Sec. and Sec. No. 208 20E N.M.P.U.
Wildcat Las New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

It is our intention to drill a well at the above location to a total depth of approximately 12,000' with rotary tools in an attempt to obtain commercial quantities of gas. All casing points will be cemented in accordance with approved methods of the U. S. Geological Survey and any other special requirements will be supplied with.

It is planned to use the following casing patterns: 13 3/8" casing to be set at 600' and cemented with approximately 650 sacks cement, cement to circulate to surface; 9 5/8" casing to be set at approximately 3,400' and cemented with approximately 1,775 sacks cement, cement to return to surface; 7" casing to be set at approximately 12,000' and cemented with approximately 1,775 sacks cement or as determined by survey. Selectively perforate and test opposite the pay zone. Approval to produce this well upon completion is also requested.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Continental Oil CompanyAddress Box 427Hobbs, New Mexico

By [Signature]
Title Asst. Dist. Supt.

I

Label 2 or medical grade will be like a little
 label made of square or at least square of
 substance of substance of like other white like
 wrapper label will be like you see in the
 of of white "T.C. 2" wrapper white wrapper
 a square of white, square white "T.C. 2" wrapper
 like substance has "T.C. 2" wrapper as seen
 of of white "T.C. 2" wrapper of white of white
 square white "T.C. 2" wrapper like substance
 as on you see other side has white wrapper
 wrapper side of white wrapper like white

FOIA b 7 - Exempt

74 75

00-124 100-124

SECRET