

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR
CONOCO INC.
3. ADDRESS OF OPERATOR
P. O. Box 460, Hobbs, N.M. 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FNL + 330' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input checked="" type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) RE-PERF <input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

5. LEASE
NM-1151
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
NMFU
8. FARM OR LEASE NAME
SANDERSON B-10
9. WELL NO.
10. FIELD OR WILDCAT NAME
EUNICE MONUMENT G/SA
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
SEC. 10, T20S, R36E
12. COUNTY OR PARISH 13. STATE
LEA NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

MIRU 3/29/84. SPOTTED 1 BBL 15% HCL-NE-FE
3713'-3756'. PERF W/2 JSPF @ 3749'-3759'
(20 PERFS). SET PKR @ 3710'. ACIDIZED W/12
BBLs 15% HCL-NE-FE. FLUSHED W/23 BBLs TFW.
SWBD. REL PKR. RAN PROD EQUIP. PMPD 0 BO
+ 168 BW IN 24 HRS 4/13/84.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED W. A. Kuttel TITLE Administrative Supervisor DATE 5/7/84

ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY GWQ TITLE _____ DATE _____
CONDITIONS OF APPROVAL MAY 11 1984

Carlsbad, NEW MEXICO

*See Instructions on Reverse Side