

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRI
(Other instruction
reverse side)

DATE
p re

Form 3160-5
Adopted August 31, 1985
LEASE DESIGNATION AND SERIAL NO.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. UNIT AGREEMENT NAME Reed Sanderson Unit
2. NAME OF OPERATOR Conoco Inc.	8. FARM OR LEASE NAME Reed Sanderson
3. ADDRESS OF OPERATOR P.O. Box 460, Hobbs, NM 88240	9. WELL NO. # 21
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface	10. FIELD AND POOL, OR WILDCAT Carmichael 7 Rivers Queen
14. PERMIT NO. 30-025-24199	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 10, T. 20S, R. 36E
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 1980' FWH, 1980' FWH 3624' DF	12. COUNTY OR PARISH New
	13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
(Other)

PULL OR ALTER CASING
MULTIPLE COMPLETION
ABANDON*
CHANGE PLANE

SUBSEQUENT REPORT OF:

WATER SHUT-OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZING
(Other)

REPAIRING WELL
ALTERING CASING
ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Notified BLM before RL. 2111 w/ 5 1/2" Arrowc 18P to 3785'. POH to 3783'. Tested csg. to 500' - held. Circ wellbore w/ 95 bbl brine. POH w/ tbg. & setting tool. 2111 w/ 08 tbg. to 3725. Surbbed tbg. 3783'. Pump 10 BBH wtr, 25 sc class "C" 14.8" cmt, 5 bbs wtr. & 8.8 bbl brine. Cmt. plug from 3783' to 3544'. Spilled 10 sks class "C" cmt. from 1432' to 1336', displaced w/ 5.2 BBH brine. Perf. a 363' w/ 4 1/2" jsp. Pumped 97 sks class "C" cmt. csg. & circ. to surface. Rig dr. Install dry hole marker. Restore location.

18. I hereby certify that the foregoing is true and correct

SIGNED W. W. Dake W. W. Dake

TITLE Administrative Supervisor

DATE 1/25/90

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE 2/26/90

Approved as to plugging of the well bore,
Listed on the back of this form until

*See Instructions on Reverse Side

RECEIVED

MAR 2 1990

OCD
HOBBS OFFICE