Form 9-331 (May 1963)

16.

UN TD STATES DEPARTMEN. OF THE INTERIOR (Other instruction verse side) GEOLOGICAL SURVEY

SUBMIT IN TRIPLE ATE

Form approved. Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO.

LC - 046164 A 6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON	WELLS
-------------------------------	-------

(Do not use this form for Dro	posals to drill or to deepen or plug back to a different reservoir. ICATION FOR PERMIT—" for such proposals.)	
1. OIL V GAS		7. UNIT AGREEMENT NAME
WE'L X GAS OTHER		
2. NAME OF OPERATOR		8. FARM OR LEASE NAME
Amerada <u>Hess Co</u>	rporation	H.W. Andrews
3. ADDRESS OF OPERATOR		9. WELL NO.
Drawer D, Monume	ent, NM 88265	2
4. LOCATION OF WELL (Report location See also space 17 below.)	n clearly and in accordance with any State requirements.	10. FIELD AND POOL, OR WILDCAT EUNICE - Monument
At surface		Grayburg - San Andres
Unit "A" 660' FN	IL abd 660' FEL	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
	15. ELEVATIONS (Show whether DF, RT, GR, etc.)	SEC 11 TWP 20 S PGE 36 E
14. PERMIT NO.	15. BLEVATIONS (Show whether Dr. RT, GR, etc.)	IN. COUNTY OF TARISH 10. STATE
		lea New Mevico

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:				
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE		PULL OR ALTER CASING MULTIPLE COMPLETE ABANDON*		WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING	REPAIRING WELL ALTERING CASING ABANDONMENT*	_
REPAIR WELL (Other)		CHANGE PLANS		(Other) (Note: Report results of m Completion or Recompletion	ultiple completion on Well Report and Log form.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

November 21, 1977 - Pulled rods and pump. Checked fill in 7" csg at 3796' and pulled 2-7/8'' tbg.

November 22, 1977 - McCullough perf Grayburg San Andres Zone in open hole w/one glass jet shot at each of the following intervals: 3763', 3768', 3769', 3771', 3772', 3774', 3776', 3778', 3789', 3790', 3791', 3792', 3793', and 3794'. Checked for fill after perforating. Ran pkr on 2-7/8'' tbg and set at 3675'. Dowell acidized and chemical squeezed Grayburg San Andres Zone in open hole from 3760' to 3801' w/4000 gal 15% NE iron stabilized acid and 3000 gal 2% KCL water mixed w/165 gal Seal-frac in stages.

November 23, 1977 - Pulled tbg and pkr. Re-ran tbg pump and rods. Resumed production.

Test of December 10, 1977 - Pumped 56 BO and 56 BW in 24 hours.

18. I hereby certify that the foregoing is true and correct SIGNED	TITLE Supv. Admin. Serv.	DATE 12-12-77
(This space for Federal or State office use)		
APPROVED BYCONDITIONS OF APPROVAL, IF ANY:	ACCE	PTED FOR RECORD

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURV HOBBS, NEW MEXICO