

COPY TO O. C. A.

Form 9-331  
Dec. 1973Form Approved.  
Budget Bureau No. 42-R1424UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well ☐ gas ☐ well ☐ other *dual o & g*
2. NAME OF OPERATOR  
*Conoco Inc.*
3. ADDRESS OF OPERATOR  
*P.O. Box 460, Hobbs, N.M. 88240*
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: *990' FSL & 1650' FEL*  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

## REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
- FRACTURE TREAT ☐
- SHOOT OR ACIDIZE ☐
- REPAIR WELL ☐
- PULL OR ALTER CASING ☐
- MULTIPLE COMPLETE ☐
- CHANGE ZONES ☐
- ABANDON\* ☐
- (other) ☐

## SUBSEQUENT REPORT OF:

- ☐
- ☐
- ☒
- ☐
- ☐
- ☐
- ☐
- ☐

APR 1 1980

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

5. LEASE  
*LC-03162.2 a*
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME  
*N.M.F.U.*
8. FARM OR LEASE NAME  
*Sanderson A*
9. WELL NO.  
*4*
10. FIELD OR WILDCAT NAME  
*Eunice Monument G-SA  
Eunice Queen Gas*
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
*Sec. 11, T-20S, R-3E*
12. COUNTY OR PARISH  
*Lea*
13. STATE  
*N.M.*
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

*MIRU 3-17-80. Tagged fill @ 3720'. Cleaned out to 3452' Perf. @ 3800'-3810', 3820'-3824', 3830'-3834' w/ 1 JSPP. Perf. @ 3648', 3656'-3658', 3661'-3664', 3680'-3684', 3692'-3696', 3706'-3708', 3719'-3737', 3744'-3746', 3770'-3774' w/ 2 JSPP. Acidized w/ 6000 gal. 15% HCl-NE-FE w/ additives. Flush & Swabbed. Spot 1000 gal. 20% HCl-NE-FE & let acid set. Pumped in TFW. Acid on formation 3 hrs. Swabbed well dry. Set pkr @ 3421', OEMA @ 3751'. Put well on production*

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED *Walter A. Dutton* TITLE *Admin. Supervisor* DATE *3/28/80*

ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

USGS-5

NMFU-4

FILE

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

TITLE \_\_\_\_\_

DATE \_\_\_\_\_

\*See Instructions on Reverse Side

7210  
OIL CONSERVATION DIV.

RECEIVED

APR 8 1980

OIL CONSERVATION DIV.