

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN THE
(Other Instructions
Apply side)

Budget Bureau No. 1004-0135
Expires August 31, 1985

3. LEASE DESIGNATION AND SERIAL NO.

LC 046 164 (a)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

H. W. Andrews

9. WELL NO.

4

10. FIELD AND POOL, OR WILDCAT

Monument - G/SA

11. SEC., T., R., W., OR BLK. AND
SURVEY OR AREA

Sec. 12, T20S, R36E

12. COUNTY OR PARISH

Lea

13. STATE

N.M.

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Amerada Hess Corporation

3. ADDRESS OF OPERATOR

Drawer D, Monument, New Mexico 88265

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1980' FSL & 660' FWL, Unit L.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, ST, OR, etc.)

3569' DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5-10 to 5-15-89

MIRU pulling unit & TOH w/rods & pump. Installed BOP, checked bottom at 3860' & TOH w/tbg. Ran 3-1/8" sand pump & cleaned out fill fr. 3860' to TD at 3885'. Ry-Co string shot Grayburg San Andres Zone OH fr. 3783' - 3885' w/400 GPF primer cord. Ran 6-5/8" x 2-7/8" Md. R pkr. set at 3760'. Acid Engr. loaded 6-5/8" csg. & tbg. & press. to 2000#. Acidized Grayburg San Andres Zone OH fr. 3784' - 3885' w/1500 gal. 15% NEFE acid. Swabbed load & TOH w/pkr. Re-ran tbg. set OE at 3880'. Removed BOP & ran pump & rods & resumed pumping well.

Test of 5-26-89: Pumped 40 b.o., 10 b.w., & 18 MCFGPD in 24 hrs. on 10 x 54" SPM.

ACCEPTED FOR RECORD

JUN 10 1989

EB

CARLSBAD, NEW MEXICO

JUN 2 11 13 AM '89

RECEIVED

18. I hereby certify that the foregoing is true and correct

SIGNED

R. L. Whaley, Jr.

TITLE Supv. Adm. Svc.

DATE 5-31-89

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side