

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLE  
(Other instructions  
verse side)

E\*  
60

Form approved  
Budget Category No. 42 R1424

5. LEASE DESIGNATION AND SERIAL NO.

LC-046164(a)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

H.W. Andrews

9. WELL NO.

6

10. FIELD AND POOL, OR WILDCAT

Unice-Monument (G-SA)

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 12, T-20-S, R-36-E

12. COUNTY OR PARISH 13. STATE

Lea

New Mexico

1. ☒ GAS ☐ OIL ☐ OTHER

2. NAME OF OPERATOR

Amerada Hess Corporation

3. ADDRESS OF OPERATOR

Drawer "D", Monument, New Mexico 88265

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)

At surface

660' FSL & 660' FWL of Sec. 12

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3565' DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

T°A°

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

Pulled production equipment. Set Cast iron bridge plug at 3750' with 10' cement on top. Perforated 6-5/8" casing with 2 shots at 3630', 3640', 3643', 3660', 3666', 3672', 3682', 3685', 3692', 3694', 3715', 3717', 3724', 3726'. Total 28 shots. Acidized perfs. 3630' to 3726' with 3000 gals. 15% NE acid using ball sealers. Swab tested. Dry. Set cast iron bridge plug at 3656' with one (1) sack cement on top. Top of cement at 3652'. Perforated 6-5/8" casing with 2 shots at: 3548', 3554', 3556', 3558', 3563', 3579', 3583', 3585', 3590', 3596'. Total 20 shots. Acidized perfs. 3548' to 3643' with 3500 gals. 15% NE acid with ball sealers. Swab tested. Non-Commercial. CLOSED ALL VALVES AND T°A°

This approval of temporary **AUG 11 1976**  
abandonment expires

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Supvr., Admin. Services

DATE

8-1-75

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD  
AUG 11 1975

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

\*See Instructions on Reverse Side