

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on Plugging Back	X

April 11, 1948

Date

Monument, New Mexico

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____
_____ Well No. 8 in the

Amerada Petroleum Corporation H. W. Andrews Company or Operator
_____ of Sec. 12, T. 20S, R. 36E, N. M. P. M.,
Monument Field, Lea County.

The dates of this work were as follows: April 9, 10, 11, 1948

Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on April 9, 1948
and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

5200' Plugged Back Depth. Plugged back with 50 sacks regular cement from 5270' to 5102' and reversed out about 15 sx cement. Went in hole with bit and found top of cement at 5130'. Drilled cement out to 5323'. Plugged back with 50 sx cement from 5320' to 5200' and reversed out about 14 sx cement at 11:30PM, 4-9-48. Drilled cement out to 5250' and perforated with Lane Wells from 5200' to 5250', 400 holes. Ran Guiberson Packer and 172 jts. of 2-7/8" OD, 6.5# Hydril Tubing with 3-4' perforated sub on bottom bull plugged and 1-4' handling sub on packer. Set packer at 5150' with bottom of tubing at 5248'.

Witnessed by K. V. Stephenson Amerada Petroleum Corporation Foreman
Name Company Title

Subscribed and sworn before me this _____
11th. day of April 19 48

Will Heide Taylor
Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name [Signature]
Position Asst. Dist. Supt.
Representing Amerada Petroleum Corporation
Company or Operator

My commission expires _____

Address Drawer D, Monument, New Mexico

Remarks:

[Signature]
Name
Title

APPROVED

APR 19 1948

THE UNIVERSITY OF CHICAGO

1961-1962

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO

THE UNIVERSITY OF CHICAGO

Handwritten signature and date