


## OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS



Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

|  |  |  |   |
|--|--|--|---|
| REPORT ON BEGINNING DRILLING OPERATIONS                    |  | REPORT ON REPAIRING WELL                       |   |
| REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL |  | REPORT ON PULLING OR OTHERWISE ALTERING CASING |   |
| REPORT ON RESULT OF TEST OF CASING SHUT-OFF                |  | REPORT ON DEEPENING WELL                       |   |
| REPORT ON RESULT OF PLUGGING OF WELL                       |  | Report on Setting Casing                       | X |

March 31, 1948

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum Corporation H. W. Andrews Well No. 8 in the  
Company or Operator Lease  
NW 1/4 N 1/4 of Sec. 12, T. 20S, R. 36E, N. M. P. M.,  
Monument Field, Lea County.

The dates of this work were as follows: March 30, 31, 1948

Notice of intention to do the work was (~~submitted~~) submitted on Form C-102 on March 30, 19 48  
and approval of the proposed plan was (~~submitted~~) obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

10488' Plugged Back Depth. Ran total of 220 joints of 5 1/2" OD, 17#, J-55, R-3, 8-RT, SS Casing New and set at 8646'. Cemented with 100 sacks of Trinity Regular Cement and plug pumped to 8605' at 1:46AM, 3-31-48. Final pressure 1000#. Have 12 Weatherford Hall Scratchers set at: 8600', 8590', 8580', 8570', 8560', 8550', 8540', 8530', 8520', 8510', 8500' and 8490'. Have 6 Baker Centralizers set at 8595', 8573', 8548', 8523', 8496' and 8471'.

Ran Schlumberger Survey to bottom at 10827' before plugging back to 10488'.

Witnessed by C. E. Telge Amerada Petroleum Corporation Farm Boss  
Name Company Title

Subscribed and sworn before me this

I hereby swear or affirm that the information given above is true and correct.

31st. day of March, 19 48

Name

Position

Representing

Asst. Dist. Supt.

Amerada Petroleum Corporation  
Company or Operator

My commission expires My Commission Expires May 9, 1948

Address Drawer D, Monument, New Mexico

Remarks:

APPROVED

Date APR 2 1948

Ray W. Anderson  
Name  
OIL & GAS INSPECTOR  
Title