

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

JUN 17 1948
RECEIVED
HOBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	<input checked="" type="checkbox"/>
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

June 14, 1948

Date

Monument, New Mexico,

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____
Amerada Petroleum Corporation W. P. Byrd Well No. 4 in the _____

Company or Operator _____ Lease _____
NE 1/4 NW 1/4 of Sec. 12, T. 20 S, R. 36 E, N. M. P. M.,
Monument Field, Los County.

The dates of this work were as follows: June 8th to June 12, 1948 Inc.

Notice of intention to do the work was ~~(cross out)~~ submitted on Form C-102 on June 7, 1948
 and approval of the proposed plan was ~~(cross out)~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED
3885' Total Depth, ran Dowell Spinner Survey twice and bottom 7 feet of hole was taking fluid while pumping at rate of 82 gallons of water per minute, fluid was standing at 820 feet from surface and fluid would start in hole as soon as pump was started. Ran Lane-Wells Gamma Ray Survey to total depth of 3885' and details from 3700' to 3885'. Plugged back from 3885' to 3862' with 140 gallons of plastic, ran 122 jts 2 7/8" OD EUE Tubing to 3856' with 6 5/8" x 2 1/2" Guiberson Type G-2 Control Head Packer set at 3724', loaded hole with 140 barrels of oil and swabbed 4 hours and recovered 48.60 barrels of oil and tubing was plugged. Pulled Tubing and unplugged tubing, gun perforated with Lane wells from 3862' to 3810' - 4 shots per foot for a total of 208 shots. C. E. Telge

Witnessed by _____ Name _____ Company _____ Title _____
Amerada Pet. Corp. Farm Boss

Subscribed and sworn before me this _____

15 day of June 1948

Will Hails Taylor
 Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name D. J. ToppPosition Asst. Dist. Supt.

Representing Amerada Pet. Corp.,
 Company or Operator

My commission expires _____

Address Drawer D, Monument, New Mexico.

Remarks:

APPROVED

Date

JUN 17 1948

Roy Garbrough
 Name

Asst. Dist. Supt.
 Title

Handwritten signature or text at the bottom left corner.